



EBRO SUSPENDED

The Power Of Geometry.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT, DIRECT / INDIRECT
MATERIALS	ALUMINIUM

The EBRO Suspended is the perfect lighting to embed a modern feel in any environment from the moment you step in. With its simple and minimalist structure. Ideal for a vast range of environments from offices to lobby areas or even retail lighting, this luminaire is a highly versatile product which will be appreciated by all wherever it's situated.


*Product is also available as surface, wall and recessed mounting styles. More details are coming soon. Please contact the office for further information.

PRODUCT CODE

EBRO SUSPENDED DIRECT

l (mm)		High Efficiency	
630x630mm	LED	53W / 5581 lm	68-F*1-F55-***-***
910x910mm	LED	79W / 8371 lm	68-F*1-F83-***-***
1190x1190mm	LED	105W / 11161 lm	68-F*1-F11-***-***
1470x1470mm	LED	132W / 13951 lm	68-F*1-F13-***-***
1750x1750mm	LED	158W / 16741 lm	68-F*1-F16-***-***
l (mm)		High Output	
630x630mm	LED	74W / 7401 lm	68-F*1-F70-***-***
910x910mm	LED	111W / 11102 lm	68-F*1-F12-***-***
1190x1190mm	LED	147W / 14802 lm	68-F*1-F14-***-***
1470x1470mm	LED	184W / 18503 lm	68-F*1-F18-***-***
1750x1750mm	LED	221W / 22203 lm	68-F*1-F22-***-***

* Luminous Flux taken with 4000K / Microprismatic Diffuser



EBRO SUSPENDED DIRECT / INDIRECT

l (mm)		High Efficiency	
630x630mm	LED	92W / 9766 lm	68-F*3-F97-***-***
910x910mm	LED	145W / 15346 lm	68-F*3-F15-***-***
1190x1190mm	LED	197W / 20926 lm	68-F*3-F20-***-***
1470x1470mm	LED	250W / 26506 lm	68-F*3-F26-***-***
1750x1750mm	LED	302W / 32086 lm	68-F*3-F32-***-***
l (mm)		High Output	
630x630mm	LED	1269W / 12952 lm	68-F*3-F12-***-***
910x910mm	LED	202W / 20353 lm	68-F*3-F19-***-***
1190x1190mm	LED	276W / 27754 lm	68-F*3-F22-***-***
1470x1470mm	LED	349W / 35155 lm	68-F*3-F35-***-***
1750x1750mm	LED	423W / 42556 lm	68-F*3-F42-***-***

* Luminous Flux taken with 4000K / Microprismatic Diffuser

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC OPAL	68-F*F-***-***-*** 68-F*H-F-***-***-***
----------------	------	----------------	--

* Nero optic available on request

CRI

80	90	80 90	68-F**F**_0**-*** 68-F**F**_0**-***
----	----	----------	--

COLOUR TEMPERATURE

3000K	4000K	3000K 4000K TW	68-F**F**_30-*** 68-F**F**_40-*** 68-F**F**_TW-J-*
TW 2700-5000K			

CONTROL

NON DIM	DALI DIM	NON DIM DALI DIM EASY AIR PIR B. DALI DIM	68-F**F**-***-K* 68-F**F**-***-J* 68-F**F**-***-Q* 68-F**F**-***-M*
EasyAir PIR/ Daylight DIM	DALI DIM BLUETOOTH		

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR 3 HR	68-F**F**-***-0* 68-F**F**-***-3*
--------------	------------------	--------------	--------------------------------------

FINISH

WHITE	BLACK	WHITE BLACK SILVER	68-F**F**-***-C 68-F**F**-***-D 68-F**F**-***-B
SILVER			

