

# FASENY SUSPENDED

Linear LG7 Lighting.

## PRODUCT DESCRIPTION

<b>MOUNTING</b>	SUSPENDED
<b>LIGHT SOURCE</b>	LED
<b>LIGHT DISTRIBUTION</b>	DIRECT-INDIRECT
<b>MATERIALS</b>	ALUMINIUM
<b>OPTIC</b>	OPAL

Contemporary and unique in design, the Faseny adds visual appeal to any modern office space; a high-quality luminaire that compliments almost any environment. The Faseny is available as stand-alone unit or a sophisticated architectural lighting system.


This office lighting LED solution offers bi-directional diffuser, this distributes light evenly, lighting the ceiling and the desk space, making it a perfect choice for LG7 linear LED office lighting. The product is easily installed with a twin drop suspension point making this an elegant and easy to install pendant light.

## PRODUCT CODE

### FASENY SUSPENDED DIRECT-INDIRECT


L (mm)	High Efficiency	
562mm	<b>LED</b> 9W / 1060 lm	41-EH3-F10-8**-0*-*
842mm	<b>LED</b> 13W / 1530 lm	41-EH3-F15-8**-0*-*
1122mm	<b>LED</b> 18W / 2120 lm	41-EH3-F21-8**-0*-*
1402mm	<b>LED</b> 24W / 2760 lm	41-EH3-F27-8**-0*-*
1682mm	<b>LED</b> 27W / 3180 lm	41-EH3-F31-8**-0*-*
1962mm	<b>LED</b> 30W / 3660 lm	41-EH3-F36-8**-0*-*
2242mm	<b>LED</b> 36W / 4240 lm	41-EH3-F42-8**-0*-*
L (mm)	High Output	
562mm	<b>LED</b> 15W / 1690 lm	41-EH3-F16-8**-0*-*
842mm	<b>LED</b> 20W / 2380 lm	41-EH3-F23-8**-0*-*
1122mm	<b>LED</b> 30W / 3560 lm	41-EH3-F35-8**-0*-*
1402mm	<b>LED</b> 34W / 4120 lm	41-EH3-F41-8**-0*-*
1682mm	<b>LED</b> 44W / 5290 lm	41-EH3-F52-8**-0*-*
1962mm	<b>LED</b> 50W / 5970 lm	41-EH3-F59-8**-0*-*
2242mm	<b>LED</b> 60W / 7130 lm	41-EH3-F71-8**-0*-*
L (mm)	Tunable White	
842mm	<b>LED</b> 24W / 2020 lm	41-EH3-F20-8TW-J0*-*
1122mm	<b>LED</b> 33W / 2680 lm	41-EH3-F26-8TW-J0*-*
1402mm	<b>LED</b> 41W / 3350 lm	41-EH3-F33-8TW-J*-*
1682mm	<b>LED</b> 49W / 4030 lm	41-EH3-F40-8TW-J*-*
1962mm	<b>LED</b> 57W / 4700 lm	41-EH3-F47-8TW-J*-*
2242mm	<b>LED</b> 65W / 5380 lm	41-EH3-F53-8TW-J*-*

\*Luminous Flux taken with 4000K / Opal Diffuser



### FASENY CORNER MODULE

L (mm)	High Efficiency	
603mm	<b>LED</b> 18W / 2120 lm	41-ECH3-F21-8**-0*-*
L (mm)	High Output	
603mm	<b>LED</b> 30W / 3560 lm	41-ECH3-F35-8**-0*-*
L (mm)	Tunable White	
603mm	<b>LED</b> 30W / 2680 lm	41-ECH3-F26-8TW-J*-*



### COLOUR TEMPERATURE

3000K	4000K	3000K	41-EH3-F**-830**-*
		4000K	41-ECH3-F**-830**-*
TW 2700-6500K		4000K	41-EH3-F**-840**-*
		TW	41-ECH3-F**-840**-*
		TW	41-EH3-F**-8TW-J*-*
			41-ECH3-F**-8TW-J*-*

### CONTROL

NON DIM	DALI DIM	NON DIM	41-EH3-F**-8**-K*-*
		DALI DIM	41-ECH3-F**-8**-K*-*
			41-EH3-F**-8**-J*-*
			41-ECH3-F**-8**-J*-*

### EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	41-EH3-F**-8**-0*-*
		3 HR	41-EH3-F**-8**-3*-*
			41-ECH3-F**-8**-3*-*

### FINISH

WHITE	BLACK	WHITE	41-EH3-F**-8**-*-C
		BLACK	41-ECH3-F**-8**-*-C
		SILVER	41-EH3-F**-8**-*-D
			41-ECH3-F**-8**-*-D
			41-EH3-F**-8**-*-B
			41-ECH3-F**-8**-*-B

### ACCESSORIES

L (mm)	Power Cable_4 Core	
2000mm	METAL	41-GE
L (mm)	Power Cable_5 Core	
2000mm	METAL	41-HE
L (mm)	Suspension Kit	
2000mm	METAL	41-U2000-E
80x80x32mm	Ceiling Cup	
	WHITE	41-EC
	BLACK	41-ED
	SILVER	41-EB
99x66mm	End Caps (x2)	
	WHITE	41-DC
	BLACK	41-DD
	SILVER	41-DB
1000mm	Pendant Profile	
	WHITE	41-EQH-C
	BLACK	41-EQH-D
	SILVER	41-EQH-B
	Straight Connector	
	METAL	41-KE
	DALI Straight Connector	41-JE
	METAL	

