

OKA SURFACE

The Class Leader.

PRODUCT DESCRIPTION

MOUNTING	SURFACE
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
OPTICS	PRISMATIC / OPAL


The OKA Suspended has all the attributes for setting a new standard for linear office lighting by making a statement in any modern office space. Designed with attention to detail, it will impress the purists with clean lines, homogeneous light and a proportionately designed suspension system.

The choice of 3 different colour temperatures suits any application and the light intensity can be dimmed with DALI. The Tunable White option allows the user to adjust the colour temperature contributing to the wellbeing of the workforce.

PRODUCT CODE

OKA SURFACE

l (mm)		High Efficiency	
1200mm	LED	26W / 3250 lm	52-F*1-F32-8**-*
1500mm	LED	31W / 3875 lm	52-F*1-F38-8**-*
2400mm	LED	52W / 6500 lm	52-F*1-F65-8**-*
3000mm	LED	62W / 7750 lm	52-F*1-F77-8**-*
		High Output	
1200mm	LED	36W / 4140 lm	52-F*1-F41-8**-*
1500mm	LED	44W / 5060 lm	52-F*1-F50-8**-*
2400mm	LED	72W / 8280 lm	52-F*1-F82-8**-*
3000mm	LED	88W / 10120 lm	52-F*1-F10-8**-*
		Tunable White	
1200mm	LED	27W / 2750 lm	52-F*1-F27-8TW-J*⁺
1500mm	LED	32W / 3529 lm	52-F*1-F35-8TW-J*⁺
2400mm	LED	54W / 5500 lm	52-F*1-F55-8TW-J*⁺
3000mm	LED	64W / 7058 lm	52-F*1-F70-8TW-J*⁺



* Luminous Flux taken with 4000K / Microprismatic Diffuser

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC OPAL	52-F*1-F**-8**-* 52-FH1-F**-8**-*
----------------	------	-------------------	--

COLOUR TEMPERATURE

3000K	4000K	3000K 4000K TW	52-F*1-F**-830-* 52-F*1-F**-840-* 52-F*1-F**-8TW-J*⁺
TW 2700K-5000K			

CONTROL

NON DIM	DALI DIM	NON DIM DALI DIM B. DALI DIM	52-F*1-F**-8**-K*⁺ 52-F*1-F**-8**-J*⁺ 52-F*1-F**-8**-M*⁺
BLUETOOTH DALI DIM			

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR 3 HR	52-F*1-F**-8**-0*⁺ 52-F*1-F**-8**-3*⁺
--------------	---------------------	--------------	--

FINISH

WHITE	BLACK	WHITE BLACK SILVER	52-F*1-F**-8**-*^{-C} 52-F*1-F**-8**-*^{-D} 52-F*1-F**-8**-*^{-B}
SILVER			

