

RIO RECESSED TRIMLESS

The Game Changer.

PRODUCT DESCRIPTION

MOUNTING

RECESSED TRIMLESS

LIGHT SOURCE

LED

LIGHT DISTRIBUTION

DIRECT

MATERIALS


ALUMINIUM

The RIO Recessed Trimless is the ultimate performance driven slim linear profile. Designed with simplicity and attention to detail, the RIO is contemporary and stylish. With its variation in mounting styles and diffusers, the RIO is a perfect example of flexible linear LED lighting. A true all-rounder, it is equally at home in an office and as linear architectural lighting. The RIO can be also specified as asymmetric wall washer for applications where illuminating a vertical wall is required, such as accent lighting or retail lighting. Used as an individual luminaire in standard size, or a continuous linear lighting system, the RIO adds a contemporary feel to any workplace or architectural space. Specified with the opal diffuser, the RIO Recessed creates clean smooth lines of light, in crisp plasterboard.

PRODUCT CODE


RIO RECESSED TRIMLESS

l (mm)	HIGH EFFICIENCY	
846	LED	1x19W / 1,749 lm* 58-B*1-F17-***.***
1126	LED	1x25W / 2,332 lm* 58-B*1-F23-***.***
1406	LED	1x31W / 2,914 lm* 58-B*1-F29-***.***
1686	LED	1x38W / 3,497 lm* 58-B*1-F34-***.***
2246	LED	1x50W / 4,663 lm* 58-B*1-F46-***.***
l (mm)	HIGH OUTPUT	
846	LED	1x27W / 2,391 lm* 58-B*1-F24-***.***
1126	LED	1x36W / 3,187 lm* 58-B*1-F31-***.***
1406	LED	1x44W / 3,984 lm* 58-B*1-F39-***.***
1686	LED	1x53W / 4,781 lm* 58-B*1-F47-***.***
2246	LED	1x71W / 6,374 lm* 58-B*1-F63-***.***




START MODULES

l (mm)	HIGH EFFICIENCY	
844	LED	1x19W / 1,749 lm* 58-BA1*1-F17-***.***
1124	LED	1x25W / 2,332 lm* 58-BA1*1-F23-***.***
1411	LED	1x31W / 2,914 lm* 58-BA1*1-F29-***.***
1684	LED	1x38W / 3,497 lm* 58-BA1*1-F34-***.***
2244	LED	1x50W / 4,663 lm* 58-BA1*1-F46-***.***
l (mm)	HIGH OUTPUT	
844	LED	1x27W / 2,391 lm* 58-BA1*1-F24-***.***
1124	LED	1x36W / 3,187 lm* 58-BA1*1-F31-***.***
1404	LED	1x44W / 3,984 lm* 58-BA1*1-F39-***.***
1684	LED	1x53W / 4,781 lm* 58-BA1*1-F47-***.***
2244	LED	1x71W / 6,374 lm* 58-BA1*1-F63-***.***




CENTRAL MODULES

l (mm)	HIGH EFFICIENCY	
842	LED	1x19W / 1,749 lm* 58-BA2*1-F17-***.***
1122	LED	1x25W / 2,332 lm* 58-BA2*1-F23-***.***
1402	LED	1x31W / 2,914 lm* 58-BA2*1-F29-***.***
1682	LED	1x38W / 3,497 lm* 58-BA2*1-F34-***.***
2242	LED	1x50W / 4,663 lm* 58-BA2*1-F46-***.***
l (mm)	HIGH OUTPUT	
842	LED	1x27W / 2,391 lm* 58-BA2*1-F24-***.***
1122	LED	1x36W / 3,187 lm* 58-BA2*1-F31-***.***
1402	LED	1x44W / 3,984 lm* 58-BA2*1-F39-***.***
1682	LED	1x53W / 4,781 lm* 58-BA2*1-F47-***.***
2242	LED	1x71W / 6,374 lm* 58-BA2*1-F63-***.***



END MODULES


l (mm)	HIGH EFFICIENCY	
844	LED	1x19W / 1,749 lm* 58-BA3*1-F17-***.***
1124	LED	1x25W / 2,332 lm* 58-BA3*1-F23-***.***
1404	LED	1x31W / 2,914 lm* 58-BA3*1-F29-***.***
1684	LED	1x38W / 3,497 lm* 58-BA3*1-F34-***.***
2244	LED	1x50W / 4,663 lm* 58-BA3*1-F46-***.***
l (mm)	HIGH OUTPUT	
844	LED	1x27W / 2,391 lm* 58-BA3*1-F24-***.***
1124	LED	1x36W / 3,187 lm* 58-BA3*1-F31-***.***
1404	LED	1x44W / 3,984 lm* 58-BA3*1-F39-***.***
1684	LED	1x53W / 4,781 lm* 58-BA3*1-F47-***.***
2244	LED	1x71W / 6,374 lm* 58-BA3*1-F63-***.***



CENTRAL CORNER 90° (HORIZONTAL)

l (mm)	HIGH EFFICIENCY	
600x600	LED	1x25W / 2,332 lm* 58-BA5*1-F25-***.***
l (mm)	HIGH OUTPUT	
600x600	LED	1x36W / 3,187 lm* 58-BA5*1-F30-***.***

*Not available with Asymmetric Reflector



OPTICS

MICROPRISMATIC	OPAL	ASYMMETRIC	PR	OP	AS

*Black Opal and Modular optics on request

CRI

80	90

COLOUR TEMPERATURE

3000K	4000K	TW 2700K-5000K	3000 K	4000 K	TW

*Luminous Flux taken at 3000K

CONTROL

NON DIM	DALI DIM	TUNABLE WHITE	NON DIM	DALI DIM	T. WHITE

*Casambi and EasyAir controls on request

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	3 HR

*Integral Emergency dimensions above than 1266 mm

FINISH

BLACK	WHITE	GREY	BLACK	WHITE	GREY