

RIO SUSPENDED

The Game Changer.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM

The RIO Suspended is the ultimate performance driven slim linear profile. Designed with simplicity and attention to detail, the RIO is contemporary and stylish. Used as an individual luminaire or a continuous linear lighting system, the RIO adds a contemporary feel to any workplace or architectural spaces, creating clean lines of light.

But the RIO is not just cool office lighting. With its variation in mounting styles and diffusers, the RIO is a perfect example of flexible linear LED lighting.

A true all-rounder, it is equally at home in an office, or as linear architectural lighting. The clean-cut illuminated corner modules invite you to play and create unique shapes in made-to-measure lengths.


PRODUCT CODE

RIO SUSPENDED DIRECT

l (mm)	LED	HIGH EFFICIENCY	58-E*1-F21-***-***
846mm	LED	1x20W / 2155 lm*	58-E*1-F21-***-***
1266mm	LED	1x28W / 3233 lm*	58-E*1-F32-***-***
1546mm	LED	1x35W / 3951 lm*	58-E*1-F39-***-***
1826mm	LED	1x41W / 4669 lm*	58-E*1-F46-***-***
2246mm	LED	1x50W / 5746 lm*	58-E*1-F57-***-***

l (mm)	LED	HIGH OUTPUT	58-E*1-F29-***-***
846mm	LED	1x27W / 2947 lm*	58-E*1-F29-***-***
1266mm	LED	1x40W / 4421 lm*	58-E*1-F44-***-***
1546mm	LED	1x49W / 5403 lm*	58-E*1-F54-***-***
1826mm	LED	1x58W / 6385 lm*	58-E*1-F63-***-***
2246mm	LED	1x71W / 7859 lm*	58-E*1-F78-***-***

* Luminous Flux taken with 4000K / Microprismatic Diffuser




CENTRAL CORNER 90° (HORIZONTAL) | DIRECT

l (mm)	LED	HIGH EFFICIENCY	58-EA5*1-F25-***-***
600x600 mm	LED	1x25W / 2332 lm*	58-EA5*1-F25-***-***

l (mm)	LED	HIGH OUTPUT	58-EA5*1-F30-***-***
600x600 mm	LED	1x36W / 3187 lm*	58-EA5*1-F30-***-***

* Not available with Asymmetric Reflector



OPTICS

MICROPRISMATIC	OPAL	ASYMMETRIC	PRISMATIC	58-EF1-F**-*30-***-***
			OPAL	58-EA*F1-F**-*30-***-***
			ASYMMETRIC	58-EH1-F**-*30-***-***
				58-EA*H1-F**-*30-***-***
				58-EB1-F**-*30-***-***
				58-EA*B1-F**-*30-***-***

*Black Opal and Modular Optics on request

CRI

80	90	80	58-E*1-F**-*80-***-***
		90	58-EA**1-F**-*90-***-***
			58-E*1-F**-*90-***-***
			58-EA**1-F**-*90-***-***

COLOUR TEMPERATURE

3000K	4000K	TW 2700K-5000K	3000K	58-E*1-F**-*30-***-***
			4000K	58-EA**1-F**-*30-***-***
				58-E*1-F**-*40-***-***
				58-EA**1-F**-*40-***-***
			TW	58-E*1-F**-*TW-***-***
				58-EA**1-F**-*TW-***-***

CONTROL

NON DIM	DALIDIM	NON DIM	58-E*1-F**-*K**-***-***
		DALI DIM	58-EA**1-F**-*K**-***-***
			58-E*1-F**-*J**-***-***
			58-EA**1-F**-*J**-***-***

*Casambi and EasyAir controls on request

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	58-E*1-F**-*0-***-***
			58-EA**1-F**-*0-***-***
		3 HR	58-E*1-F**-*3-***-***
			58-EA**1-F**-*3-***-***

*Integral Emergency dimensions above than 1266 mm


FINISH

BLACK	WHITE	GREY	BLACK	58-E*1-F**-*D-***-***
			WHITE	58-EA**1-F**-*D-***-***
			GREY	58-E*1-F**-*C-***-***
				58-EA**1-F**-*C-***-***
				58-E*1-F**-*B-***-***
				58-EA**1-F**-*B-***-***

RIO DIRECT START MODULES

l (mm)	LED	HIGH EFFICIENCY	58-EA1*1-F17-***-***
844mm	LED	1x19W / 1749 lm*	58-EA1*1-F17-***-***
1124mm	LED	1x25W / 2332 lm*	58-EA1*1-F23-***-***
1404mm	LED	1x31W / 2914 lm*	58-EA1*1-F29-***-***
1684mm	LED	1x38W / 3497 lm*	58-EA1*1-F34-***-***
2444mm	LED	1x50W / 4663 lm*	58-EA1*1-F46-***-***


l (mm)	LED	HIGH OUTPUT	58-EA1*1-F24-***-***
844mm	LED	1x27W / 2391 lm*	58-EA1*1-F24-***-***
1124mm	LED	1x36W / 3187 lm*	58-EA1*1-F31-***-***
1404mm	LED	1x44W / 3984 lm*	58-EA1*1-F39-***-***
1684mm	LED	1x53W / 4781 lm*	58-EA1*1-F47-***-***
2444mm	LED	1x71W / 6374 lm*	58-EA1*1-F63-***-***



RIO DIRECT CENTRAL MODULES

l (mm)	LED	HIGH EFFICIENCY	58-EA2*1-F17-***-***
842mm	LED	1x19W / 1749 lm*	58-EA2*1-F17-***-***
1122mm	LED	1x25W / 2332 lm*	58-EA2*1-F23-***-***
1402mm	LED	1x31W / 2914 lm*	58-EA2*1-F29-***-***
1682mm	LED	1x38W / 3497 lm*	58-EA2*1-F34-***-***
2442mm	LED	1x50W / 4663 lm*	58-EA2*1-F46-***-***


l (mm)	LED	HIGH OUTPUT	58-EA2*1-F24-***-***
842mm	LED	1x27W / 2391 lm*	58-EA2*1-F24-***-***
1122mm	LED	1x36W / 3187 lm*	58-EA2*1-F31-***-***
1402mm	LED	1x44W / 3984 lm*	58-EA2*1-F39-***-***
1682mm	LED	1x53W / 4781 lm*	58-EA2*1-F47-***-***
2442mm	LED	1x71W / 6374 lm*	58-EA2*1-F63-***-***



RIO DIRECT END MODULES

l (mm)	LED	HIGH EFFICIENCY	58-EA3*1-F17-***-***
844mm	LED	1x19W / 1749 lm*	58-EA3*1-F17-***-***
1124mm	LED	1x25W / 2332 lm*	58-EA3*1-F23-***-***
1404mm	LED	1x31W / 2914 lm*	58-EA3*1-F29-***-***
1684mm	LED	1x38W / 3497 lm*	58-EA3*1-F34-***-***
2444mm	LED	1x50W / 4663 lm*	58-EA3*1-F46-***-***

l (mm)	LED	HIGH OUTPUT	58-EA3*1-F24-***-***
844mm	LED	1x27W / 2391 lm*	58-EA3*1-F24-***-***
1124mm	LED	1x36W / 3187 lm*	58-EA3*1-F31-***-***
1404mm	LED	1x44W / 3984 lm*	58-EA3*1-F39-***-***
1684mm	LED	1x53W / 4781 lm*	58-EA3*1-F47-***-***
2444mm	LED	1x71W / 6374 lm*	58-EA3*1-F63-***-***



RIO SUSPENDED

The Game Changer.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - INDIRECT
MATERIALS	ALUMINIUM

The RIO Suspended is the ultimate performance driven slim linear profile. Designed with simplicity and attention to detail, the RIO is contemporary and stylish. Used as an individual luminaire or a continuous linear lighting system, the RIO adds a contemporary feel to any workplace or architectural spaces, creating clean lines of light.

But the RIO is not just cool office lighting. With its variation in mounting styles and diffusers, the RIO is a perfect example of flexible linear LED lighting.


A true all-rounder, it is equally at home in an office, or as linear architectural lighting. The clean-cut illuminated corner modules invite you to play and create unique shapes in made-to-measure lengths.

PRODUCT CODE

RIO SUSPENDED DIRECT - INDIRECT

l (mm)	LED	HIGH EFFICIENCY	
846mm	LED	1x34W / 4222 lm*	58-E*3-F35-***-***
1266mm	LED	1x52W / 6525 lm*	58-E*3-F65-***-***
1546mm	LED	1x65W / 8060 lm*	58-E*3-F80-***-***
1826mm	LED	1x76W / 9595 lm*	58-E*3-F95-***-***
2246mm	LED	1x94W / 11897 lm*	58-E*3-F10-***-***
l (mm)	LED	HIGH OUTPUT	
846mm	LED	1x48W / 5774 lm*	58-E*3-F47-***-***
1266mm	LED	1x74W / 8923 lm*	58-E*3-F89-***-***
1546mm	LED	1x91W / 11022 lm*	58-E*3-F11-***-***
1826mm	LED	1x108W / 13121 lm*	58-E*3-F14-***-***
2246mm	LED	1x134W / 16271 lm*	58-E*3-F13-***-***

* Luminous Flux taken with 4000K / Microprismatic Diffuser



CENTRAL CORNER 90° (HORIZONTAL) | DIRECT - INDIRECT

l (mm)	LED	HIGH EFFICIENCY	
600x600 mm	LED	1x25W / 2332 lm*	58-EA5*3-F25-***-***
600x600 mm	LED	1x36W / 3187 lm*	58-EA5*3-F30-***-***

* Not available with Asymmetric Reflector

OPTICS

MICROPRISMATIC	OPAL	ASYMMETRIC	PRISMATIC	58-EF3-F**-*-*-* 58-EA*F3-F**-*-*-* 58-EH*3-F**-*-*-* 58-EA*H3-F**-*-*-*
			OPAL	58-EB3-F**-*-*-* 58-EA*B3-F**-*-*-*
			ASYMMETRIC	

*Black Opal and Modular Optics on request

CRI

80	90	80	58-E*3-F**-*G**-* 58-EA**3-F**-*G**-* 58-E*3-F**-*G**-* 58-EA**3-F**-*G**-*
		90	

COLOUR TEMPERATURE

3000K	4000K	TW 2700K-5000K	3000K	58-E*3-F**-*30-*** 58-EA**3-F**-*30-*** 58-E*3-F**-*40-*** 58-EA**3-F**-*40-*** 58-E*3-F**-*TW-J** 58-EA**3-F**-*TW-J**
			4000K	
			TW	

CONTROL

NON DIM	DALIDIM	NON DIM	58-E*3-F**-*K** 58-EA**3-F**-*K** 58-E*3-F**-*J** 58-EA**3-F**-*J**
		DALI DIM	

*Casambi and EasyAir controls on request

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	58-E*3-F**-*0-*** 58-EA**3-F**-*0-*** 58-E*3-F**-*3-*** 58-EA**3-F**-*3-***
		3 HR	


*Integral Emergency dimensions above than 1266 mm

FINISH

BLACK	WHITE	GREY	BLACK	58-E*3-F**-*D 58-EA**3-F**-*D 58-E*3-F**-*C 58-EA**3-F**-*C 58-E*3-F**-*B 58-EA**3-F**-*B
			WHITE	
			GREY	


RIO DIRECT - INDIRECT START MODULES

l (mm)	LED	HIGH EFFICIENCY	
844mm	LED	1x34W / 3596 lm*	58-EA1*3-F35-***-***
1124mm	LED	1x47W / 4691 lm*	58-EA1*3-F46-***-***
1404mm	LED	1x59W / 5941 lm*	58-EA1*3-F59-***-***
1684mm	LED	1x71W / 7192 lm*	58-EA1*3-F71-***-***
2444mm	LED	1x96W / 10150 lm*	58-EA1*3-F10-***-***
l (mm)	LED	HIGH OUTPUT	
844mm	LED	1x49W / 4703 lm*	58-EA1*3-F47-***-***
1124mm	LED	1x66W / 6413 lm*	58-EA1*3-F64-***-***
1404mm	LED	1x84W / 8123 lm*	58-EA1*3-F81-***-***
1684mm	LED	1x102W / 9832 lm*	58-EA1*3-F98-***-***
2444mm	LED	1x137W / 13252 lm*	58-EA1*3-F13-***-***



RIO DIRECT - INDIRECT CENTRAL MODULES

l (mm)	LED	HIGH EFFICIENCY	
842mm	LED	1x34W / 3596 lm*	58-EA2*3-F35-***-***
1122mm	LED	1x47W / 4691 lm*	58-EA2*3-F46-***-***
1402mm	LED	1x59W / 5941 lm*	58-EA2*3-F59-***-***
1682mm	LED	1x71W / 7192 lm*	58-EA2*3-F71-***-***
2442mm	LED	1x96W / 10150 lm*	58-EA2*3-F10-***-***
l (mm)	LED	HIGH OUTPUT	
842mm	LED	1x49W / 4703 lm*	58-EA2*3-F47-***-***
1122mm	LED	1x66W / 6413 lm*	58-EA2*3-F64-***-***
1402mm	LED	1x84W / 8123 lm*	58-EA2*3-F81-***-***
1682mm	LED	1x102W / 9832 lm*	58-EA2*3-F98-***-***
2442mm	LED	1x137W / 13252 lm*	58-EA2*3-F13-***-***



RIO DIRECT - INDIRECT END MODULES

l (mm)	LED	HIGH EFFICIENCY	
844mm	LED	1x34W / 3596 lm*	58-EA3*3-F35-***-***
1124mm	LED	1x47W / 4691 lm*	58-EA3*3-F46-***-***
1404mm	LED	1x59W / 5941 lm*	58-EA3*3-F59-***-***
1684mm	LED	1x71W / 7192 lm*	58-EA3*3-F71-***-***
2444mm	LED	1x96W / 10150 lm*	58-EA3*3-F10-***-***
l (mm)	LED	HIGH OUTPUT	
844mm	LED	1x49W / 4703 lm*	58-EA3*3-F47-***-***
1124mm	LED	1x66W / 6413 lm*	58-EA3*3-F64-***-***
1404mm	LED	1x84W / 8123 lm*	58-EA3*3-F81-***-***
1684mm	LED	1x102W / 9832 lm*	58-EA3*3-F98-***-***
2444mm	LED	1x137W / 13252 lm*	58-EA3*3-F13-***-***

