



RYDAL SUSPENDED

Halo Circular Pendant.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - DIRECT / INDIRECT
MATERIALS	ALUMINIUM
OPTIC	MICROPRIMATIC / OPAL

The RYDAL adds an instant visual presence to any commercial lighting requirement. Thanks to its flexible nature, the RYDAL is an ideal architectural luminaire for bespoke designs. The RYDAL can be tailored to your design with a diameter of up to 8m.

The 100 mm wide and 87mm deep body is ideal for large spaces or atrium's where a strong visual presence is required. Emitting direct and indirect light, these LED luminaires distribute homogeneous soft light.


The smaller sizes are a great choice for office lighting, breakout spaces and circulation areas. The light is uniform, efficient and comfortable.

PRODUCT CODE

RYDAL SUSPENDED DIRECT

L (mm)	High Efficiency	
Ø600 x 87mm	LED 22W / 2120 lm	47-E*1-F21-8**-*0-*
Ø850 x 87mm	LED 44W / 4210 lm	47-E*1-F42-8**-*0-*
Ø1200 x 87mm	LED 54W / 5090 lm	47-E*1-F50-8**-*0-*
Ø1500 x 87mm	LED 67W / 6360 lm	47-E*1-F63-8**-*0-*
Ø2000 x 87mm	LED 84W / 7770 lm	47-E*1-F77-8**-*0-*
Ø2500 x 87mm	LED 104W / 9650 lm	47-E*1-F96-8**-*0-*
Ø3000 x 87mm	LED 127W / 11800 lm	47-E*1-F11-8**-*0-*
High Output		
Ø600 x 87mm	LED 32W / 3020 lm	47-E*1-F30-8**-*0-*
Ø850 x 87mm	LED 60W / 5620 lm	47-E*1-F56-8**-*0-*
Ø1200 x 87mm	LED 73W / 6980 lm	47-E*1-F69-8**-*0-*
Ø1500 x 87mm	LED 92W / 8730 lm	47-E*1-F87-8**-*0-*
Ø2000 x 87mm	LED 114W / 10580 lm	47-E*1-F10-8**-*0-*
Ø2500 x 87mm	LED 142W / 13140 lm	47-E*1-F13-8**-*0-*
Ø3000 x 87mm	LED 173W / 16060 lm	47-E*1-F16-8**-*0-*

* Luminous Flux taken with 4000K / Microprismatic Diffuser



RYDAL SUSPENDED DIRECT / INDIRECT

L (mm)	High Efficiency	
Ø600 x 87mm	LED 28W / 2710 lm	47-E*3-F27-8**-*0-*
Ø850 x 87mm	LED 54W / 4940 lm	47-E*3-F49-8**-*0-*
Ø1200 x 87mm	LED 66W / 6190 lm	47-E*3-F61-8**-*0-*
Ø1500 x 87mm	LED 82W / 7740 lm	47-E*3-F77-8**-*0-*
Ø2000 x 87mm	LED 107W / 9920 lm	47-E*3-F99-8**-*0-*
Ø2500 x 87mm	LED 128W / 11800 lm	47-E*3-F11-8**-*0-*
Ø3000 x 87mm	LED 163W / 15020 lm	47-E*3-F15-8**-*0-*
High Output		
Ø600 x 87mm	LED 45W / 4060 lm	47-E*3-F40-8**-*0-*
Ø850 x 87mm	LED 64W / 5960 lm	47-E*3-F59-8**-*0-*
Ø1200 x 87mm	LED 88W / 8260 lm	47-E*3-F82-8**-*0-*
Ø1500 x 87mm	LED 110W / 10330 lm	47-E*3-F10-8**-*0-*
Ø2000 x 87mm	LED 147W / 13510 lm	47-E*3-F13-8**-*0-*
Ø2500 x 87mm	LED 175W / 16060 lm	47-E*3-F16-8**-*0-*
Ø3000 x 87mm	LED 222W / 20440 lm	47-E*3-F20-8**-*0-*

* Luminous Flux taken with 4000K / Microprismatic Diffuser

OPTICS

MICROPRIMATIC	OPAL	PRISMATIC OPAL	47-EF*-F**-8**-*0-*	47-EH*-F**-8**-*0-*
---------------	------	----------------	---------------------	---------------------

COLOUR TEMPERATURE

3000K	4000K	3000K	47-E**-F**-830-*0-*
		4000K	47-E**-F**-840-*0-*

CONTROL

NON DIM	DALI DIM	NON DIM	47-E**-F**-8**-*0-*
		DALI DIM	47-E**-F**-8**-*J0-*
		DALI DIM B.	47-E**-F**-8**-*M0-*
		NON DIM PIR	47-E**-F**-8**-*R0-*
		EASY AIR PIR	47-E**-F**-8**-*Q0-*
DALI DIM BLUETOOTH	NON DIM PIR Sensor		
EasyAir PIR Daylight DIM			

*CASAMBI (integrated controls)

FINISH

WHITE	BLACK	WHITE	47-E**-F**-8**-*0-C
		BLACK	47-E**-F**-8**-*0-D
		SILVER	47-E**-F**-8**-*0-B
SILVER			

SCAN RYDAL PRODUCT



SCAN RYDAL PROJECT

