

SENIA SUSPENDED

The Power Of Geometry.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT, DIRECT / INDIRECT
MATERIALS	ALUMINIUM


Product is also available as Surface, Wall and Recessed mounting styles.

More details are coming soon. Please contact the office for further information.

PRODUCT CODE

SENIA SUSPENDED DIRECT

L (mm)	High Efficiency	
566 mm	LED 39W / 4311 lm	69-F*1-F43-***-***
846 mm	LED 57W / 6465 lm	69-F*1-F64-***-***
1126 mm	LED 84W / 9669 lm	69-F*1-F96-***-***
	High Output	
566 mm	LED 54W / 5895 lm	69-F*1-F58-***-***
846 mm	LED 81W / 8841 lm	69-F*1-F88-***-***
1126 mm	LED 120W / 13263 lm	69-F*1-F13-***-***



* Luminous Flux taken with 4000K / Microprismatic Diffuser

SENIA SUSPENDED DIRECT / INDIRECT

L (mm)	High Efficiency	
566 mm	LED 66W / 8061 lm	69-F*3-F80-***-***
846 mm	LED 102W / 12666 lm	69-F*3-F12-***-***
1126 mm	LED 156W / 19575 lm	69-F*3-F19-***-***
	High Output	
566 mm	LED 93W / 11022 lm	69-F*3-F11-***-***
846 mm	LED 144W / 17322 lm	69-F*3-F17-***-***
1126 mm	LED 222W / 26769 lm	69-F*3-F26-***-***

* Luminous Flux taken with 4000K / Microprismatic Diffuser

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC OPAL	69-F*F***-***-*** 69-F*H***-***-***
----------------	------	-------------------	--

* Nero optic available on request

CRI

80	90	80 90	69-F**F**g**-* 69-F**F**g**-*
----	----	----------	----------------------------------

COLOUR TEMPERATURE

3000K	4000K	3000K 4000K TW	69-F**F**g0**-* 69-F**F**g0**-* 69-F**F**TW-J**
TW 2700-5000K			

CONTROL

NON DIM	DALI DIM	NON DIM DALI DIM EASY AIR PIR DALI DIM B.	69-F**F**-* 69-F**F**-* 69-F**F**-* 69-F**F**-*
EasyAir PIR/ Daylight DIM	DALI DIM BLUETOOTH		

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR 3 HR	69-F**F**-* 69-F**F**-*
--------------	---------------------	--------------	----------------------------

FINISH

WHITE	BLACK	WHITE BLACK SILVER	69-F**F**-* 69-F**F**-* 69-F**F**-*
SILVER			

SCAN
SENIA
PRODUCT

