



SUNA TRACK

The Soft Spot.

PRODUCT DESCRIPTION


MOUNTING	TRACK
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM

Slim, tubular and minimalist - the LED track spotlight, Suna can meet multiple lighting requirements across many commercial spaces, from retail to workplace. Made from die-cast aluminium, and available in black, white and grey as standard*, the Suna offers clean lines with a contemporary feel to create an overall superb finish.



PRODUCT CODE

SUNA TRACK




1 (mm)	Suna Track Ø60mm	
180mm	LED 1x 14W / 1000lm	75-HZ*1-F10-930-K0*
		<small>*4000K available on request. *Optional lens are clear glass or frosted glass.</small>



BEAM ANGLE

		24°	75-HZ31-F10-930-K0*
		36°	75-HZ51-F10-930-K0*

FINISH

		BLACK	75-HZ*1-F10-930-K0-D
		WHITE	75-HZ*1-F10-930-K0-C
		GREY	75-HZ*1-F10-930-K0-B



SUNA TRACK

The Soft Spot.

PRODUCT DESCRIPTION


MOUNTING	TRACK
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM

Slim, tubular and minimalist - the LED track spotlight, Suna can meet multiple lighting requirements across many commercial spaces, from retail to workplace. Made from die-cast aluminium, and available in black, white and grey as standard*, the Suna offers clean lines with a contemporary feel to create an overall superb finish.

PRODUCT CODE

SUNA TRACK

1 (mm)	Suna Track Ø70mm	
180mm	LED 1x 19W / 1650lm	75-HZ*2-F16-***-K0-*
<small>*Optional: anti-glare, barn door and honey comb.</small>		



BEAM ANGLE

	20°	75-HZ2-F16-***-K0-*
	30°	75-HZ4-F16-***-K0-*
	45°	75-HZ6-F16-***-K0-*

CRI

	90	75-HZ*2-F16-9**-K0-*
	80	75-HZ*2-F16-840-K0-*
<small>*3000K not available in CRI 80</small>		

COLOUR TEMPERATURE

	3000K	75-HZ*2-F16-930-K0-*
	4000K	75-HZ*2-F16-*40-K0-*
<small>*Luminous Flux take at 3000K *3000K not available in CRI 80</small>		

FINISH

	BLACK	75-HZ*2-F16-***-K0-D
	WHITE	75-HZ*2-F16-***-K0-C



SUNA TRACK

The Soft Spot.

PRODUCT DESCRIPTION

MOUNTING	TRACK
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM

Slim, tubular and minimalist - the LED track spotlight, Suna can meet multiple lighting requirements across many commercial spaces, from retail to workplace. Made from die-cast aluminium, and available in black, white and grey as standard*, the Suna offers clean lines with a contemporary feel to create an overall superb finish.

PRODUCT CODE

SUNA TRACK

Suna Track Ø95mm										
1 (mm)										
240mm	<table border="0"> <tr> <td>LED</td> <td>1x 9.5W / 1100lm</td> <td>75-HZ*3-F11-***-*0-*</td> </tr> <tr> <td>LED</td> <td>1x 18.5W / 2100lm</td> <td>75-HZ*3-F21-***-*0-*</td> </tr> <tr> <td>LED</td> <td>1x 26W / 2850lm</td> <td>75-HZ*3-F28-***-*0-*</td> </tr> </table>	LED	1x 9.5W / 1100lm	75-HZ*3-F11-***-*0-*	LED	1x 18.5W / 2100lm	75-HZ*3-F21-***-*0-*	LED	1x 26W / 2850lm	75-HZ*3-F28-***-*0-*
LED	1x 9.5W / 1100lm	75-HZ*3-F11-***-*0-*								
LED	1x 18.5W / 2100lm	75-HZ*3-F21-***-*0-*								
LED	1x 26W / 2850lm	75-HZ*3-F28-***-*0-*								
*Nordic Track Adapter										
*Optional on request Barn Door										

BEAM ANGLE

		15°	75-HZ13-F***-***-*0-*
		24°	75-HZ33-F***-***-*0-*
		36°	75-HZ53-F***-***-*0-*

CRI

		80	75-HZ*3-F**.*0**-*0-*
		90	75-HZ*3-F**.*9**-*0-*

COLOUR TEMPERATURE

		3000K	75-HZ*3-F**.*30-*0-*
		4000K	75-HZ*3-F**.*40-*0-*
*Luminous Flux take at 3000K			

CONTROL

		NON DIM	75-HZ*3-F**-***-K0-*
		DALI DIM	75-HZ*3-F**-***-J0-*

FINISH

		BLACK	75-HZ*3-F**-***-*0-D
		WHITE	75-HZ*3-F**-***-*0-C
		GREY	75-HZ*3-F**-***-*0-B