

TALLA SURFACE

The Timeless.

PRODUCT DESCRIPTION

MOUNTING	SURFACE
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - DIRECT/INDIRECT
MATERIALS	ALUMINIUM
OPTICS	MICROPRISMATIC / OPAL

The architectural office lighting Talla uses the idea of basic geometrical shapes and timeless appearance to produce a luminaire which delivers simplicity at its best. Variation in sizes, multiple colour choices and the selection of dimming options means the Talla can now add a personality to any space.


The option of an opal diffuser gives a clean and contemporary look, with the evenly distributed light enhancing the details of a building's architecture.

PRODUCT CODE

TALLA SURFACE DIRECT

L (mm)	High-Efficiency	
400x62mm	LED 1x 17W /1820lm	21-F*1-F18-8***-*
500x62mm	LED 1x 27W /3400lm	21-F*1-F34-8***-*
600x62mm	LED 1x 28W /3790lm	21-F*1-F37-8***-*
850x62mm	LED 1x 53W /6960lm	21-F*1-F69-8***-*
1150x87mm	LED 1x 80W /10340lm	21-F*1-F10-8***-*
High-Output		
400x62mm	LED 1x 28W /3250lm	21-F*1-F32-8***-*
500x62mm	LED 1x 41W /4900lm	21-F*1-F49-8***-*
600x62mm	LED 1x 40W /5280lm	21-F*1-F52-8***-*
850x62mm	LED 1x 73W /9360lm	21-F*1-F93-8***-*
1150x87mm	LED 1x 106W /13920lm	21-F*1-F13-8***-*


* Luminous Flux taken with 4000K / Microprismatic Diffuser



TALLA SURFACE DIRECT / INDIRECT

L (mm)	High-Efficiency	
400x62mm	LED 1x 15W /2010lm	21-F*3-F20-8***-*
500x62mm	LED 1x 27W /3400lm	21-F*3-F36-8***-*
600x62mm	LED 1x 22W /3120lm	21-F*3-F31-8***-*
850x62mm	LED 1x 44W /6120lm	21-F*3-F61-8***-*
1150x87mm	LED 1x 91W /12120lm	21-F*3-F12-8***-*
High-Output		
400x62mm	LED 1x 26W /3360lm	21-F*3-F33-8***-*
500x62mm	LED 1x 41W /5450lm	21-F*3-F54-8***-*
600x62mm	LED 1x 36W /5080lm	21-F*3-F50-8***-*
850x62mm	LED 1x 74W /9960lm	21-F*3-F99-8***-*
1150x87mm	LED 1x 121W /16300lm	21-F*3-F16-8***-*

* Luminous Flux taken with 4000K / Microprismatic Diffuser



OPTICS

MICROPRISMATIC	OPAL	PRISMATIC OPAL	21-F**-F**-8**-* 21-F**-F**-8**-*
----------------	------	-------------------	--------------------------------------

COLOUR TEMPERATURE

3000K	4000K	3000K	21-F**-F**-830-***
		4000K	21-F**-F**-840-***
		TW	21-F**-F**-8TW-J**
TW 2700-6500K			

*TW not available for ø1150 x 87

CONTROL

NON DIM	DALIDIM	NON DIM	21-F**-F**-8**-K**
		DALI DIM	21-F**-F**-8**-J**
		B. DALI DIM	21-F**-F**-8**-M**
DALI DIM BLUETOOTH			

*PIR Sensor available on request

EMERGENCY

NON EMERGENCY	3 HOUR EMERGENCY	0 HR	21-F**-F**-8**-0**
		3 HR	21-F**-F**-8**-3**

FINISH

BLACK	WHITE	BLACK	21-F**-F**-8**-*D
		WHITE	21-F**-F**-8**-*C
		SILVER	21-F**-F**-8**-*B
SILVER			

SCAN
TALLA
PRODUCT



SCAN
TALLA
PROJECT

