



# TINTO SUSPENDED

The Power Of Geometry.

## PRODUCT DESCRIPTION

|                           |                           |
|---------------------------|---------------------------|
| <b>MOUNTING</b>           | SUSPENDED                 |
| <b>LIGHT SOURCE</b>       | LED                       |
| <b>LIGHT DISTRIBUTION</b> | DIRECT, DIRECT / INDIRECT |
| <b>MATERIALS</b>          | ALUMINIUM                 |

Product is also available as Surface, Wall and Recessed mounting styles.


More details are coming soon. Please contact the office for further information.

## PRODUCT CODE

### TINTO SUSPENDED DIRECT

| L (mm)      | High Efficiency          |                           |
|-------------|--------------------------|---------------------------|
| 566 mm      | <b>LED</b> 26W / 2874 lm | <b>70-F*1-F28-***-***</b> |
| 846mm       | <b>LED</b> 38W / 4310 lm | <b>70-F*1-F43-***-***</b> |
| 1126mm      | <b>LED</b> 56W / 6466 lm | <b>70-F*1-F64-***-***</b> |
| High Output |                          |                           |
| 566 mm      | <b>LED</b> 36W / 3930 lm | <b>70-F*1-F39-***-***</b> |
| 846mm       | <b>LED</b> 54W / 5894 lm | <b>70-F*1-F58-***-***</b> |
| 1126mm      | <b>LED</b> 80W / 8842 lm | <b>70-F*1-F88-***-***</b> |


\* Luminous Flux taken with 4000K / Microprismatic Diffuser



### TINTO SUSPENDED DIRECT / INDIRECT

| L (mm)      | High Efficiency            |                           |
|-------------|----------------------------|---------------------------|
| 566 mm      | <b>LED</b> 44W / 5374 lm   | <b>70-F*3-F53-***-***</b> |
| 846mm       | <b>LED</b> 46W / 8444 lm   | <b>70-F*3-F84-***-***</b> |
| 1126mm      | <b>LED</b> 104W / 13050 lm | <b>70-F*3-F13-***-***</b> |
| High Output |                            |                           |
| 566 mm      | <b>LED</b> 62W / 7348 lm   | <b>70-F*3-F73-***-***</b> |
| 846mm       | <b>LED</b> 96W / 11548 lm  | <b>70-F*3-F11-***-***</b> |
| 1126mm      | <b>LED</b> 148W / 17846 lm | <b>70-F*3-F17-***-***</b> |

\* Luminous Flux taken with 4000K / Microprismatic Diffuser



### OPTICS

|                |      |                   |   |
|----------------|------|-------------------|---|
| MICROPRISMATIC | OPAL | PRISMATIC<br>OPAL | <b>70-F**F**...***</b><br><b>70-FH**F**...***</b> |
|----------------|------|-------------------|---|

\* Nero optic available on request

### CRI

|    |    |          |  |
|----|----|----------|--|
| 80 | 90 | 80<br>90 | <b>70-F**F**...g**...*</b><br><b>70-F**F**...g**...*</b> |
|----|----|----------|--|

### COLOUR TEMPERATURE

|                  |       |                      |   |
|------------------|-------|----------------------|---|
| 3000K            | 4000K | 3000K<br>4000K<br>TW | <b>70-F**F**...g0-***</b><br><b>70-F**F**...g0-***</b><br><b>70-F**F**...TW-J**</b> |
| TW<br>2700-5000K |       |                      |   |

### CONTROL

|                             |                       |  |  |
|-----------------------------|-----------------------|--|--|
| NONDIM                      | DALIDIM               | NON DIM<br>DALI DIM<br>EASY AIR PIR<br>DALI DIM B. | <b>70-F**F**...-K**</b><br><b>70-F**F**...-J**</b><br><b>70-F**F**...-Q**</b><br><b>70-F**F**...-M**</b> |
| EasyAir PIR<br>Daylight DIM | DALI DIM<br>BLUETOOTH |  |  |

### EMERGENCY

|              |                     |              |   |
|--------------|---------------------|--------------|---|
| NO EMERGENCY | 3 HOUR<br>EMERGENCY | 0 HR<br>3 HR | <b>70-F**F**...-Q-*</b><br><b>70-F**F**...-Q3-*</b> |
|--------------|---------------------|--------------|---|

### FINISH

|        |       |                          |   |
|--------|-------|--------------------------|---|
| WHITE  | BLACK | WHITE<br>BLACK<br>SILVER | <b>70-F**F**...-C</b><br><b>70-F**F**...-D</b><br><b>70-F**F**...-B</b> |
| SILVER |       |                          |   |

