



TURIA SUSPENDED

The Power Of Geometry.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT, DIRECT / INDIRECT
MATERIALS	ALUMINIUM

The TURIA Suspended is a performance driven linear profile based on an equilateral triangle. It is simple, contemporary and sleek. Used as an individual pendant luminaire or a cluster of triangles, Turia adds a playful feel to any workplace or architectural spaces, guaranteed to stand out. And the best thing about Turia? The luminaire is supplied pre assembled as one unit, meaning a super easy installation!

*Product is also available as surface, recessed trim and trimless mounting styles.

PRODUCT CODE

TURIA SUSPENDED DIRECT		
l (mm)	High Efficiency	
910mm	LED 54W / 5670 lm	67-FH1-F56-***-**-*
1190mm	LED 72W / 7560 lm	67-FH1-F75-***-**-*
	High Output	
910mm	LED 75.6W / 7938 lm	67-FH1-F79-***-**-*
1190mm	LED 100.8W / 10584 lm	67-FH1-F10-***-**-*

* Luminous Flux taken with 4000K / Microprismatic Diffuser

TURIA SUSPENDED DIRECT / INDIRECT		
l (mm)	High Efficiency	
910mm	LED 108W / 11340 lm	67-FH3-F11-***-**-*
1190mm	LED 144W / 15120 lm	67-FH3-F15-***-**-*
	High Output	
910mm	LED 151.2W / 15876 lm	67-FH3-F15-***-**-*
1190mm	LED 201.6W / 21168 lm	67-FH3-F21-***-**-*

* Luminous Flux taken with 4000K / Microprismatic Diffuser

CRI			
80	90	80	67-FH*-F**-g**-***-*
		90	67-FH*-F**-g**-***-*

COLOUR TEMPERATURE			
3000K	4000K	3000K	67-FH*-F**-*30-***-*
		4000K	67-FH*-F**-*40-***-*

CONTROL			
NON DIM	DALI DIM	NON DIM	67-FH*-F**-***-K*-*
		DALI DIM	67-FH*-F**-***-J*-*
		EASY AIR PIR	67-FH*-F**-***-Q*-*
		B. DALI DIM	67-FH*-F**-***-M*-*
EasyAir PIR/Daylight DIM	DALI DIM BLUETOOTH	*Sensors available on request: Non-Dim PIR Non-Dim PIR/Daylight Dali-Dim PIR Dali-Dim PIR/Daylight	

EMERGENCY			
NO EMERGENCY	3 HOUR EMERGENCY	0 HR	67-FH*-F**-***-*0-*
		3 HR	67-FH*-F**-***-*3-*

FINISH			
WHITE	BLACK	WHITE	67-FH*-F**-***-**-C
		BLACK	67-FH*-F**-***-**-D
		SILVER	67-FH*-F**-***-**-B
SILVER			

