



VENTA

Track Lighting.

PRODUCT DESCRIPTION

MOUNTING	TRACK
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM

The Venta can be truly unique, with front rings available in standard black, white and grey* or compliment your design scheme with alternative RAL colours. Mix and match front ring colours to create a unique design. It is substantial enough to make a presence in the workplace, making it an ideal luminaire for contemporary office lighting or display lighting in museums, retail or hotels.

PRODUCT CODE

VENTA TRACK

Venta Track Ø58mm	
1 (mm)	
130mm	LED 1x 9.5W/1160lm* 74-HZ*1-F11-***-0*

BEAM ANGLE

		20° 74-HZ21-F11-***-0*
		36° 74-HZ51-F11-***-0*

CRI

		90 74-HZ*1-F11-930-0*
		80 74-HZ*1-F11-840-0*

*CRI 90 just available in 3000K
*CRI 80 just available in 4000K

COLOUR TEMPERATURE

		3000K 74-HZ*1-F11-930-0*
		4000K 74-HZ*1-F11-840-0*

*Luminous Flux take at 3000K

CONTROL

		NON DIM 74-HZ*1-F11-***-K0*
		DALI DIM 74-HZ*1-F11-***-J0*
		BLUETOOTH 74-HZ*1-F11-***-M0*

FINISH

		BLACK 74-HZ*1-F11-***-0-D
		WHITE 74-HZ*1-F11-***-0-C



VENTA

Track Lighting.

PRODUCT DESCRIPTION


MOUNTING	TRACK
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM

The Venta can be truly unique, with front rings available in standard black, white and grey* or compliment your design scheme with alternative RAL colours. Mix and match front ring colours to create a unique design. It is substantial enough to make a presence in the workplace, making it an ideal luminaire for contemporary office lighting or display lighting in museums, retail or hotels.

PRODUCT CODE

VENTA TRACK

Venta Track Ø80mm										
1 (mm)										
170mm	<table border="0"> <tr> <td>LED</td> <td>1x 14W / 1550lm*</td> <td>74-HZ*2-F15-***-0-*</td> </tr> <tr> <td>LED</td> <td>1x 18.5W / 2100lm*</td> <td>74-HZ*2-F21-***-0-*</td> </tr> <tr> <td>LED</td> <td>1x 27W / 2850lm*</td> <td>74-HZ*2-F28-***-0-*</td> </tr> </table>	LED	1x 14W / 1550lm*	74-HZ*2-F15-***-0-*	LED	1x 18.5W / 2100lm*	74-HZ*2-F21-***-0-*	LED	1x 27W / 2850lm*	74-HZ*2-F28-***-0-*
LED	1x 14W / 1550lm*	74-HZ*2-F15-***-0-*								
LED	1x 18.5W / 2100lm*	74-HZ*2-F21-***-0-*								
LED	1x 27W / 2850lm*	74-HZ*2-F28-***-0-*								
*Optional lens are clear glass or frosted glass.										



FINISH

BLACK	WHITE	BLACK	74-HZ*2-F**-***-0-D
		WHITE	74-HZ*2-F**-***-0-C
		GREY	74-HZ*2-F**-***-0-B
	GREY		

BEAM ANGLE

15°	24°	15°	74-HZ*2-F**-***-0-D
		24°	74-HZ*2-F**-***-0-C
		36°	74-HZ*2-F**-***-0-B

CRI

90	80	90	74-HZ*2-F**-g**-0-*
		80	74-HZ*2-F**-g**-0-*

COLOUR TEMPERATURE

3000K	4000K	3000K	74-HZ*2-F**-*30-0-*
		4000K	74-HZ*2-F**-*40-0-*
*Luminous Flux take at 3000K			

CONTROL

NON DIM	DALI DIM	NON DIM	74-HZ*2-F**-***-K0-*
		DALI DIM	74-HZ*2-F**-***-J0-*
		BLUETOOTH	74-HZ*2-F**-***-M0-*
	BLUETOOTH		