

CASSIOPEIA AL3950



Benefits

- Distinct contemporary styling lends itself to a wide range of urban environments

Features

- Lighting head comprises of a cast aluminium unit and front bezel, incorporating a brightened spun aluminium reflector
- Cast aluminium support arms carrying the upper reflector canopy
- Upper reflector canopy incorporates a secondary reflector system, a multifaceted reflector which provides precise control of reflected light
- Post top mounted on to a stylised galvanised column finished polyester powder coated in RAL9007 Gunmetal

Note: column height as stated is total height, to the upper lantern canopy

Colours

- RAL9007 Gunmetal



	Lamp wattage and type	Lamp holder	Description	Weight (kg)*	Windage (m²)*
AL3952	150W HCI-T	G12	Secondary Reflector, Integral Control Gear System	19.5	0.18

*Max in range.




Column options

6m		5m		4m			6m	5m	4m
Fixed						Shaft diameter (mm)	127	127	127
Straight Tubular	S061/AL3950/9007	S051/AL3950/9007	S041/AL3950/9007						
Accessories						Root length (mm)	1000	800	800
ELS987/6A	Single phase, cut-out, 6A, termination plate up to 10mm² loop in/out Dimensions 68mm(W), 53m(D), 170mm(H)								
Column hot dip galvanised and polyester powder coated to RAL9007 Gunmetal.						Flange plate (circular) (mm)	290 Type 0	290 Type 0	290 Type 0
						Door opening (mm) (80mm clear width)	400 x 100	400 x 100	400 x 100
						Cable entry (root) (mm)	150 x 50	150 x 50	150 x 50


Straight tubular




Key features




Dimensions & Mounting
60mm/114mm spigot
Mounting height:
4m – 6m



Maintenance
Access the lamp and control gear by removing glass cover



AL3952
150W HCI-T
Mounting height: 5m



AL3952
150W HCI-T
Mounting height: 5m

All dimensions are in mm.

Full photometry available on our website www.abacuslighting.com