

**Special Features**

- ▲ HYGIENIC VANDAL RESISTANT DESIGN
- ▲ NO GAPS OR CREVICES FOR CONCEALMENT OF CONTRABAND
- ▲ INTEGRAL UNDERSHROUD TO CONCEAL PIPEWORK

**Description**

The security wash basin is extremely resistant to impact damage and vandalism. Designed for wall mounting in secure locations with concealed duct services, the wash basin has no crevices where contraband can be concealed. The wash basin top is extended to form an integral undershroud to conceal the supply and waste pipework. The wash basin outlet trap should be installed within the service duct.

**Construction**

The security wash basin is manufactured in one piece without joints or crevices from grade 304 stainless steel, with all exposed surfaces polished to a satin finish. The wash basin top, which incorporates a rear upstand for ease of cleaning and hygiene, is extended to form an integral undershroud.

The security wash basin is produced with two tap holes and is supplied as standard with a combined waste and overflow fitting with captive plug. Also provided with the security wash basin is a waste outlet pipe with a 90° bend and four M12 x 150 mm long bolts to suit walls up to 118 mm thick. As an option, for walls up to 268 mm thick, M12 x 300 mm long bolts can be supplied.



**Options**

- ▲ Non-standard waste fitting
- ▲ Non-standard tap hole sizes
- ▲ Stainless steel tap hole blank
- ▲ M12 x 300 mm long bolts (for 119 – 268 mm thick walls)
- ▲ Water controllers, taps and valves

**Order Codes and Technical Specification**

Please refer to the Technical Specification Sheet