

SHOWER PANEL SURFACE MOUNTED

PRODUCT CODE

521

MAY 2010

Special Features

- ▲ HYGIENIC VANDAL RESISTANT DESIGN
- ▲ EASY TO INSTALL
- ▲ COMPLETE WITH ISOLATING/SERVICE VALVE
- ▲ FACTORY ASSEMBLED WITH SPRAY HEAD, VALVE AND INTERCONNECTING PIPEWORK
- ▲ OPTIONAL WHITE Enviro-Glaze FINISH

Description

The surface mounted shower panel is supplied as a complete assembly fitted with a pneumatic, push button, valve, spray head and interconnecting pipework terminating with an isolation/service valve. The panel is ideal for installing where multiple shower facilities are required, such as leisure centres, sports facilities, campsites, schools, colleges and military barracks, particularly where vulnerable exposed surface mounted valves and spray heads are prone to misuse, damage or vandalism. Although suitable for connecting to exposed high level supply pipework, the shower panel can be easily adapted on-site to accept a back entry concealed water connection. As an option to the standard stainless steel finish the shower panel is available in a range of Enviro-Glaze colours.

Construction

The surface mounted shower panel is manufactured in one piece without joints or crevices from grade 304 stainless steel, with all exposed surfaces polished to a satin finish. The panel is factory assembled with either a fixed vandal resistant spray head or a fixed shower arm with swivel spray head, a timed flow push button pneumatic valve adjustable to give 2 to 60 seconds flow duration and interconnecting pipework terminating in an isolating/service valve. Designed for connecting to a surface mounted temperature controlled water supply the shower panel pipework can be easily modified, on installation, to suit a concealed water supply connection.

Options

- ▲ Enviro-Glaze coloured finish.

Order Codes and Technical Specification

Please refer to the Technical Specification Sheet

