




Granite finish  
with optional sensor  
operated taps



White with  
optional lever  
operated taps




White

Grey

Yellow

Blue



Pink

Green

Red

Orange

Standard colours:  
These colours are an indicative guide  
only as colour rendition varies  
between screens and printers



### Special Features

- ▲ VANITY OR WALL MOUNTING OPTION
- ▲ PLEASING WAVE EFFECT DESIGN
- ▲ INDIVIDUAL WASH AREAS
- ▲ SPLIT LEVEL DUAL HEIGHT OPTION TO INCLUDE DISABLED USERS AND CHILDREN
- ▲ TAPLANDING DESIGN
- ▲ EASY TO CLEAN AND MAINTAIN
- ▲ SMOOTH NON-POROUS HYGIENIC DESIGN
- ▲ WIDE CHOICE OF COLOURS
- ▲ CAN BE SUPPLIED WITH OPTIONAL SENSOR TAPS OR MECHANICAL TAPS

### Description

The Rezina Wave solid surface wash trough has a fashionable contoured design and is ideally suited for use in schools, universities, nightclubs, bars, restaurants, office and hotel washrooms, where a modern aesthetically pleasing appearance is desired. The Wave wash trough can be supplied in a choice of standard or special colours with a tap landing (for deck mounted outlets). The solid surface wash trough is designed for mounting to vanity units (by others) with the option for wall mounting if desired. A split level dual height option can be supplied to facilitate use by disabled users and children. The Rezina Wave trough is supplied in a range of standard lengths providing individual washing areas for two to six users.

### Construction

The Wave solid surface wash trough is manufactured from a blend of acrylic resin, natural pigments and aluminium hydroxide to give a natural stone appearance. A two stage thermal curing process at high temperature gives the solid surface material superb strength and durability. The wash trough is formed with individual wash areas blended into a single unit with attractive wave effect internal contours. Designed for deck mounting, or "sit-on" type installation onto an existing vanity unit type construction (by others). Optional metal brackets can be supplied for wall mounting the trough. Available in six standard lengths, all solid surface wash troughs are supplied with an unslotted flush grated waste fitting and tap holes as required.

### Sizes

Available in standard lengths: 1000, 1500, 2000, 2500 and 3000mm.

### Options

- ▲ Special colours
- ▲ Metal wall mounting brackets
- ▲ Split level dual height to include use by disabled users and children
- ▲ "Non-Touch" sensor taps
- ▲ Mechanical taps

### Order Codes and Technical Specification

Please refer to the Technical Specification Sheet