

ACRYPOL+

FROM ACRYPOL PRODUCTS LTD



ACRYPOL+ roof coating was specifically developed to provide a solution for carrying out the day to day maintenance requirements of those involved in roof waterproofing protection. As with most water penetration problems associated with leaking roofs, the need to carry out remedial repairs is very rarely possible during long spells of inclement weather. This is mainly due to the fact that in order to carry out an effective long term repair to leaking roofs, it is generally necessary to ensure that the surfaces to be treated are completely dry.

ACRYPOL+ can be applied during damp weather conditions and at the same time provide a long term solution to the problem. The all-weather application properties, combined with the simplicity of application, makes this product a particularly attractive proposition to those employing their own labour for general property maintenance. The versatility of **ACRYPOL+** is acknowledged widely by Municipal Authorities and Maintenance Contractors throughout the United Kingdom.

ALL WEATHER APPLICATION WATERPROOF ROOF COATING

ACRYPOL+ available in PACKS OF 4 x 5kgs or DRUMS OF 20kgs

T 01925 213655 E info@acrypolproducts.co.uk W www.acrypolproducts.co.uk
A 4 Asher Court, Lyncastle Way, Barleycastle Lane, Appleton, Warrington WA4 4ST





ACRYPOL+ is an acrylic resin dispersed in a solvent to form a semi-liquid paste. The coating film dries into a tough durable elastic overlay that prevents the passage of water, yet is chemically structured to allow trapped moisture to evaporate, thus avoiding the formation of blisters. A specific feature is incorporated with added fibres, fibres that act like a built-in scrim. These fibres interlace when the coating is applied – filling and bridging gaps and cracks (up to 10mm wide). The fibres increase the tensile strength of the dry film making it more durable – **A BIG PLUS!**

ACRYPOL+ is available in two standard colours, Solar White for maximum solar protection of the roof surface, and Medium Grey generally used for day to day patching repairs where it is preferable to blend the coating into surrounding building material colours.

In certain areas where minimal structural movement occurs and tensile strength is not of paramount importance, eg. corrugated asbestos sheeting, or where spray application of the coating is required, the product is available without fibres under the description of standard ACRYPOL which is also available in Solar White or Medium Grey colours.

SOLAR PROTECTION WARNING

Due to the deterioration of the earth's ozone layer. We strongly recommend the specification of SOLAR WHITE **ACRYPOL+** for maximum solar reflectivity and protection against the increased intensity and damage caused by ultra violet rays.

TECHNICAL DATA

COVERAGE

1-2kg/m² average
(See application guide)

DRYING TIME

2-3 days depending on ambient temperature and ventilation

FLASH POINT

21oc - 55oc

WATER TIGHTNESS

Several years with lid secure

SHELF LIFE

12 months with lid secure, low odour

COLOUR

Solar White or Medium Grey
(other colours available on special order)

CLEANING

Use Acrypol Cleaner to clean equipment

STORAGE

Store in even moderate temperature

