




Ancon Building Products

n55Plus



Lateral Restraint Slip Ties

By Ancon Building Products

Detailed description

Stainless steel lateral restraint slip ties designed for use as lateral restraint ties for movement joints. Available as channel ties and cavity ties and manufactured from austenitic stainless steel grade 1.4301 (304).

Debonding sleeves are used on plain ended wall ties at vertical movement joints. The tie will restrain the masonry against lateral wind loads but the sleeve will allow the masonry to expand or contract.

Product guidance - As Standard

Material:

Austenitic stainless steel.

Options

Ancon PPB:

- Plain ended wall tie with 7 mm fixing hole designed to be used with plastic debonding sleeves at vertical movement joints in masonry walls.
- The PPB is available in five lengths: 125 mm, 150 mm, 175 mm, 200 mm and 225 mm.

Ancon PPV:

- Plain ended wall tie with 8 x 30 mm fixing slot.
- The PPV is designed to be used with plastic debonding sleeves at vertical movement joints in masonry walls.
- The PPV is available in five lengths: 125 mm, 150 mm, 175 mm, 200 mm and 225 mm.

Ancon PPS:

- Plain ended wall tie to be used with plastic debonding sleeves at vertical movement joints in masonry walls.
- The PPS is available in three lengths: 175 mm, 225 mm and 250 mm.

Ancon PP21:

- Channel tie for use with 21/18 Omega channel.
- The PP21 is designed to be used with plastic debonding sleeves at vertical movement joints in masonry walls.

- The PP21 is available in five lengths: 125 mm, 150 mm, 175 mm, 200 mm and 225 mm.

Product specification

Manufacturer

- Name:	Ancon Building Products
- Web:	www.ancon.co.uk
- Email:	info@ancon.co.uk
- Tel:	+44 (0)114 275 5224
- Fax:	+44 (0)114 276 8543
- Address:	President Way,President Park,Sheffield,South Yorkshire S4 7UR

Product reference	Lateral Restraint Slip Ties
-------------------	-----------------------------

Type	Ancon PP21 channel tie Ancon PPB wall tie Ancon PPS wall tie Ancon PPV wall tie
------	--

Length	125 mm - PPB/ PPV/ PP21. 150 mm - PPB/ PPV/ PP21. 175 mm - PPB/ PPV/ PPS/ PP21. 200 mm - PPB/ PPV/ PP21. 225 mm - PPB/ PPV/ PPS/ PP21. 250 mm - PPS.
--------	---

Material	Stainless steel grade 1.4301 (304)
----------	------------------------------------