


Ancon Building Products

n55Plus



Frame Cramps

By Ancon Building Products

Detailed description

Frame cramps can be fixed to concrete, steelwork or masonry and have a single 7 mm diameter hole or an 8 mm x 30 mm vertical slot. Ancon M6 Single Expansion bolts are recommended for fixing to concrete, set screws or self-drilling screws for steelwork, and suitable plugs and screws for fixing to masonry.

Frame cramps should have a minimum embedment of 50 mm in the outer leaf. Taking site tolerances into account, Ancon suggests tie lengths which achieve a greater embedment.

Product guidance - As Standard

Material:

Austenitic stainless steel.

Options

Ancon SPB:

Frame cramp with 7 mm fixing hole.

- Size:

75 mm/ 100 mm/ 125 mm/ 150 mm/ 175 mm/ 200 mm.

Ancon SDB:

Frame cramp with drip and 7 mm fixing hole.

- Size:

125 mm/ 150 mm/ 175 mm/ 200 mm/ 225 mm.

Ancon PPB:

Frame cramp with debonding sleeve and 7 mm fixing hole.

- Size:

125 mm/ 150 mm/ 175 mm/ 200 mm/ 225 mm.

Ancon PPV:

Frame cramp with debonding sleeve and 8 x 30 mm fixing slot.

- Size:

125 mm/ 150 mm/ 175 mm/ 200 mm/ 225 mm.

Ancon SPV:

Frame cramp with 8x30 mm fixing slot.

- Size:

75 mm/ 100 mm/ 125 mm/ 150 mm/ 175 mm/ 200 mm.

Ancon SDV:

Frame cramp with drip and 8x30 mm fixing slot.

- Size:

125 mm/ 150 mm/ 175 mm/ 200 mm/ 225 mm.

Product specification

Manufacturer

- Name: Ancon Building Products
- Web: www.ancon.co.uk
- Email: info@ancon.co.uk
- Tel: +44 (0)114 275 5224
- Fax: +44 (0)114 276 8543
- Address: President Way,President Park,Sheffield,South Yorkshire S4 7UR

Product reference PPB Frame Cramp Tie
 PPV Frame Cramp Tie
 SDB Frame Cramp Tie
 SDV Frame Cramp Tie
 SPB Frame Cramp Tie
 SPV Frame Cramp Tie

Length 75 mm - SPB/ SPV.
 100 mm - SPB/ SPV.
 125 mm - SPB/ SDB/ SPV/ SDV/ PPB/ PPV.
 150 mm - SPB/ SDB/ SPV/ SDV/ PPB/ PPV.
 175 mm - SPB/ SDB/ SPV/ SDV/ PPB/ PPV.
 200 mm - SPB/ SDB/ SPV/ SDV/ PPB/ PPV.
 225 mm - SDB/ SDV/ PPB/PPV