



Declaration of Performance

Declaration Number: A0030-01-EN

ANCON hereby declares that the product range identified as,

PPB-HD, 110-225mm

conforms to the provisions of,

ZA Annex, EN 845-1: 2003 +A1: 2008

as an,

Asymmetrical Slip Tie covered in clause 1 of the standard

Intended Use: Heavy duty slip tie for connecting a new masonry leaf to an existing structure whilst allowing in-plane movement

Notified Body: CERAM Research Limited
Queens Road, Penkhull
STOKE-ON-TRENT ST4 7LQ
United Kingdom
Tel: +44 (0)1782 764444

Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Shear Load Capacity: **2690N**
Durability: **Material/coating reference 3, Steel grade 1.4301**
Dangerous Substances: **None**

Conditions

Cavity Width: **max. 10mm**
Embedment Depth: **100-215mm**
Minimum Mortar Class: **Type M4 (iii)**
Minimum Mortar Joint Width: **10mm**
Recommended Spacing: **As required**

Authorised by:

Stuart Maxwell, Managing Director, on 2nd July 2013

Manufactured by:

Ancon[®]
BUILDING PRODUCTS

Ancon Building Products
President Way
President Park
Sheffield S4 7UR
United Kingdom

Tel: +44 (0)114 275 5224
Fax: +44 (0)114 276 8543
Email: info@ancon.co.uk
Web: www.ancon.co.uk
Twitter: @AnconUK