

Ancon Building Products

n55Plus



Two-Part Tie

By Ancon Building Products

Detailed description

Two part tie designed for cavities between 150 and 300 mm. One part is built into the inner leaf of masonry; the other part is fixed as the outer leaf is built. An embedment of 75 mm is required at each end. The inner tie is usually manufactured in lengths of 170 mm with variation in the cavity width being accommodated by the length of the outer section. Where insulation thickness is in excess of 60mm, the inner section should be longer than the standard 170 mm to ensure the connection between the two parts is made in the open cavity. Ancon two-part ties sustain loads which exceed the requirements for a Type 2 tie to PD 6697 for cavities up to 300 mm. Type 3 performance is achieved at the standard tie spacing for wider cavities up to 400mm. Insulation retaining clips can be supplied to fit the inner section.

Product guidance - As Standard

Material:

Austenitic stainless steel.

Product specification

Manufacturer

- Name: Ancon Building Products
- Web: www.ancon.co.uk
- Email: info@ancon.co.uk
- Tel: +44 (0)114 275 5224
- Fax: +44 (0)114 276 8543
- Address: President Way,President Park,Sheffield,South Yorkshire S4 7UR

Product reference Two-Part Tie
Length ___ mm - To suit cavity width, with an insulation thickness of ??? mm.
Material Stainless steel grade 1.4301 (304)