



## Overview

---

The ModeLED range presents a decorative surface mounted circular luminaire incorporating high output white LEDs. ModeLED provides long life and low energy lighting in areas such as corridors and toilets where minimal maintenance is important.

## Features

---

- Available in two diameters
- 330mm / 1200lm LED output or 400mm / 1550lm LED output
- Available with mains only or maintained emergency options
- Available with detector option
- Meets with current Part L compliance, achieving over 60lm/W
- Twist-on lock diffuser
- DALI dimmable versions available

## Materials and Finishes


---

Body	Aluminium
Controller	TP(b) Acrylic
Finish	White as standard. Brushed Silver option.

## Technical Details


---

Gear            Integral Electronic LED Driver  
Light Source   High Power White LED



## Photometrics

---




### MOD400

Effective Output    1550 lm  
SHR NOM            1.50  
SHR MAX            1.647  
SHR MAX TRANS    1.869

## Dimensions

---



	<b>D</b>	<b>H</b>
MOD330	326	98
MOD400	395	113

## Ordering

---

All versions supplied including LED light source.

Order Code	Description	Light Source	Weight (kg)
MOD330	ModeLED 330mm	18W 1200lm 4000K LED	2.1
MOD400	ModeLED 400mm	24W 1550lm 4000K LED	2.6

### Suffix

DAL	Touch Dim (see accessory DC1PM) / Digital Addressable Lighting Interface (DALI)
BS	Brushed Silver Front Bezel
M010	10m Integral Microwave Detector
E	Integral 3hr Maintained Emergency

Note. DAL and M010 options are not available within the same luminaire.

### Accessories

DC1PM	Push to Make Switch for use with Touch Dim or Switch Dim gear
-------	---

IP20



CE





**Apollo Lighting Ltd**

Unit D9 Cross Green Approach  
Leeds  
LS9 0SG

Tel: 0113 240 5511

Fax: 0113 240 5151

Web: [www.apollolighting.co.uk](http://www.apollolighting.co.uk)

