



<b>Width</b>	456 mm
<b>Height</b>	609 mm
<b>Depth</b>	392 mm

<b>Flue type</b>	Conventional flue	
<b>Gas Appliance Category</b>	I3P	
<b>Gas Type</b>	G31 (Propane)	G30 (Butane)
<b>Supply Pressure</b> (measured at test elbow)	37 Mbar	29 Mbar
<b>Injector</b>	Stereomatic 120	
<b>Oxypilot type</b>	Erta PG-82-330	
<b>Nominal Heat Input (Qn)</b> (gross, maximum rate)	4.4 kW	4.5 kW
<b>Gas consumption at Max. rate</b>	0.157 m <sup>3</sup> /h	0.121 m <sup>3</sup> /h
<b>Minimum heat input</b>	1.8 kW (gross)	2.7 kW (gross)
<b>Gas consumption at Min. rate</b>	0.061 m <sup>3</sup> /h	0.074 m <sup>3</sup> /h
<b>Gas connection</b>	8mm compression	
<b>Remote gas valve</b>	TESC 01 RF868-15	
<b>Countries of destination</b>	GB & IE	
<b>Efficiency Class 1</b>	C	
<b>Space heating emissions NOx (GCV)</b>	97 mg/kWh	98 mg/kWh
<b>Hearth requirement</b>	12mm thick and of non-combustible material. Hearth must extend 150mm / 6 inch in front of appliance	

## Product Fiche

<b>Supplier name</b>	Arada
<b>Product Code</b>	ECBGAS-M-LPG-S3
<b>Energy Efficiency Class</b>	C
<b>Energy Efficiency Index</b>	79.9
<b>Direct Heat Output</b>	4.5 kW
<b>Nominal Heat Output: High</b>	4.5 kW
<b>Nominal Heat Output: Low</b>	-
<b>Indirect Heating Functionality</b>	No
<b>Indirect Heat Output</b>	N/A
<b>Useful Energy Efficiency Net CV : High</b>	-
<b>Useful Energy Efficiency Net CV : Low</b>	-
<b>Heat Output Control</b>	Electronic room temperature control plus
<b>Permanent Pilot Power kW</b>	N/A

**Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:**

Product should be installed in accordance with local building regulations. The installer must be Gas Safe Registered. Appliance will become very hot during use.

## Minimum distance to materials

Position	Non-combustible material	Combustible material
Above	100 mm	300 mm
Back	50 mm	300 mm
Left	100 mm	300 mm
Right	100 mm	300 mm



## Product Fiche

<b>Supplier name</b>	Arada
<b>Product Code</b>	ECBGAS-M-NG-S3
<b>Energy Efficiency Class</b>	B
<b>Energy Efficiency Index</b>	79.9
<b>Direct Heat Output</b>	5 kW
<b>Nominal Heat Output: High</b>	5 kW
<b>Nominal Heat Output: Low</b>	-
<b>Indirect Heating Functionality</b>	No
<b>Indirect Heat Output</b>	N/A
<b>Useful Energy Efficiency Net CV : High</b>	-

<b>Useful Energy Efficiency Net CV : Low</b>	-
<b>Heat Output Control</b>	Electronic room temperature control plus day timer
<b>Permanent Pilot Power kW</b>	N/A

**Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:**  
 Product should be installed in accordance with local building regulations. The installer must be Gas Safe Registered. Appliance will become very hot during use.

## Minimum distance to materials

Position	Non-combustible material	Combustible material
Above	100 mm	300 mm
Back	50 mm	300 mm
Left	100 mm	300 mm
Right	100 mm	300 mm

<b>Width</b>	456 mm
<b>Height</b>	609 mm
<b>Depth</b>	392 mm
<b>Flue type</b>	Conventional flue
<b>Gas appliance category</b>	I2H
<b>Gas Type</b>	G20 (Natural Gas)
<b>Supply Pressure</b> (measured at test elbow)	20 Mbar
<b>Injector</b>	Stereomatic 320
<b>Oxypilot type</b>	Erta PG-82-330
<b>Nominal Heat Input (Q<sub>n</sub>)</b>	5 kW (gross, maximum rate)
<b>Gas consumption at Max. rate</b>	0.47 m <sup>3</sup> /h
<b>Minimum heat input</b>	2.3 kW (gross)
<b>Gas consumption at Min. rate</b>	0.22 m <sup>3</sup> /h
<b>Gas connection</b>	8mm compression
<b>Remote gas valve</b>	TESC 01 RF868-15
<b>Countries of destination</b>	GB & IE
<b>Efficiency Class 1</b>	B
<b>Space heating emissions NO<sub>x</sub> (GCV)</b>	95 mg/kWh
<b>Hearth requirement</b>	12mm thick and of non-combustible material. Hearth must extend 150mm / 6 inch in front of appliance