



## Sensorflow 21 Washbasin Tall Spout Electronic Sensor, Battery

### Illustrated

**A4122** Sensorflow 21 washbasin mounted tall spout with integral sensor, anti vandal laminar flow outlet, copper tube inlet, servicing valve and filter, battery

### Configuration options

#### Material

Chrome Plated Brass

#### Weights

A4122 4.20KG

#### Colours

Chromium plated (AA)  
Brushed Steel (GN)

#### Flow rates

4.7 Litres per minute @ 3 bar pressure

#### Special Notes

Designed to be supplied with pre-mixed water. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900. The sensor is set to work in the normal handwashing position. All spouts supplied complete with individual solenoid valve, copper tube inlet and combined servicing valve and filter. Spouts with integral sensors detect hands within the sensing range and the solenoid valve is opened. Automatically shuts off if sensor is obstructed for a maximum of 55 seconds. Stand alone battery powered unit. Flow rates, regulated to 5 Litres per minute or optional flow straightener outlet 2.6 Litres per minute @ 0.1 bar

### Frequently used applications

Education	Factory
General Healthcare	Hotels
Office	Public Building
Pubs and Clubs	Retail
Sports and Leisure	Vandal Risk

#### Features

Water Saving

#### Accreditations

WRAS  
Water Label  
WTL

*Armitage  
Shanks*

Email: [info@idealspec.co.uk](mailto:info@idealspec.co.uk)  
Tel: 0870 122 8822  
Fax: 0870 122 8282  
Web: [www.idealspec.co.uk](http://www.idealspec.co.uk)

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.



Date created:25/01/2016