

ARROW ARCHITECTURAL

DOOR CONTROLS

ARROW 516VP

HEAVY DUTY VARIABLE POWER DOOR CLOSER



516VP fitted with Polished
Chrome Standard cover

Suitable for:

Offices, School Corridors, Bank Entrances, Restaurants, Pubs, Shop Doors, Hospital Wards, Municipal Buildings, Libraries, Museums, Theatres, Pubs, Restaurants, Clubs and Hotels.

Power size: Closing Force: 1–6 Fig. 1 Pullside, Fig.6 Pushside, Fig.61 Pushside Transom. Backcheck available.

Design:

Individual controls for door speed and latching fitted as standard.

Suitable for both left and right hand opening.

Supplied with Uni-Pack (adjustable) arms and brackets; ensures the door closer can be applied and fitted in regular arm, parallel arm and transom mounting formats as standard.

Optional Backcheck available.

Optional Delayed Action available.

Cover finishes:

A range of stylish cover options are available, including Stainless Steel, Bright Chrome, Satin Chrome, Polished Brass, Satin Brass, Bronze, Satin Nickel, Polished Nickel. Covers are also available in painted finishes to RAL standard – details upon request.

Cover formats available: Standard and Flowline.

CE marked – Certified for fitting to fire doors.

Patented Product.

ARROW 516VP HEAVY DUTY VARIABLE POWER DOOR CLOSER

Options		Certified for fitting to fire doors
516VP	Heavy Duty door closer, Power size 1–6, Variable Power.	✓
516VP/BC	Heavy Duty door closer, Power size 1–6, Variable Power, with Backcheck.	✓
516VP/DA	Heavy Duty door closer, Power size 1–6, Variable Power, with Delayed Action.	
516VP/BC/DA	Heavy Duty door closer, Power size 1–6, Variable Power, with Backcheck and Delayed Action.	

Applications	EN Classifications.
Fig. 1	3 8 1/6 1 1 3
Parallel Arm Fig. 6	3 8 1/5 1 1 3
Transom Fig. 61	3 8 1/6 1 1 3

CE	Fully CE marked to BS EN1154.
Fire Testing	Fire tested to BS EN 1634 part 1 for timber doors up to 120 minutes and steel doors up to 240 minutes.
Certifire	Certifire Approved. CF497.

Adjustable Power Setting	Max Door Width (mm)	Door Mass (kg)	Min Closing moment	
			4°	88° to 92°
1–6	1400	120	54	18

Body Dimensions (mm)			Standard	Flowline
	Length	275	281	302
	Height	60	75	75
	Depth	47	49	49

Arrow Architectural

Tything Road, Arden Forest Industrial Estate, Alcester, Warwickshire B49 6ES United Kingdom.

Tel: +44 (0) 1789 762 575 Fax: +44 (0) 1789 762 673

email: info@arrow-architectural.com



Manufactured in the United Kingdom.

In keeping with our policy of continuous improvement, we reserve the right to vary without notice any technical specification stated.

WWW.ARROW-ARCHITECTURAL.COM