

## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Plaster	<b>CABLE LENGTH:</b>	Not Applicable
<b>MAIN MATERIAL:</b>	Plaster	<b>GROSS WEIGHT:</b>	1.02 (Kg)
<b>DIMENSIONS:</b>	H:115mm W:115mm D:40mm	<b>CLASS:</b>	CE (Class I)
<b>INSTALLATION ORIENTATION:</b>	Install in to Existing Ceiling	<b>IP RATING:</b>	IP20
<b>CUT OUT HOLE:</b>	L: 150mm W: 150mm	<b>BATHROOM ZONE:</b>	Zone 3
<b>RECESS DEPTH:</b>	150 (mm)	<b>VOLTAGE:</b>	Mains 230 (V)
<b>FIRE RATING:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Not Suitable for: Mounting on flammable materials/Covering with thermal insulation


### LAMP

<b>LIGHT SOURCE:</b>	GU10	<b>MACADAM ELIPSE:</b>	Not Applicable
<b>MAXIMUM WATTAGE:</b>	50W Max	<b>UGR:</b>	To Be Advised
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	Lamp Dependant
<b>LAMP INCLUDED?</b>	No	<b>TILT ADJUSTMENT ANGLE:</b>	30 (Degrees)
<b>LUMINOUS FLUX:</b>	Lamp Dependant	<b>ROTATION ADJUSTMENT ANGLE:</b>	360 (Degrees)
<b>COLOUR TEMP:</b>	Lamp Dependant	<b>AVERAGE LIFESPAN:</b>	Lamp Dependant
<b>CRI:</b>	Lamp Dependant	<b>L70:</b>	Not Applicable
<b>R9:</b>	Lamp Dependant		

### ELECTRICAL

<b>SWITCHED:</b>	Not Applicable	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER / BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Lamp Dependant	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	Lamp Dependant
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER / BALLAST INCLUDED?</b>	Not Applicable

## ADDITIONAL INFORMATION



BOX QUANTITY x 6

# PRODUCT ELEVATIONS

---

