



PRODUCT SPECIFICATION

GENERAL

<b>FINISH:</b>	Matt Nickel	<b>CABLE LENGTH:</b>	Not Applicable
<b>MAIN MATERIAL:</b>	Metal - Zinc	<b>GROSS WEIGHT:</b>	3.53 (lbs)
<b>DIMENSIONS:</b>	H: 80mm W: 200mm D: 125mm H: 3.15" W: 7.87" D: 4.92"	<b>CLASS:</b>	cETLus (Class 1)
<b>INSTALLATION ORIENTATION:</b>	Wall Mount - Horizontal	<b>LISTING LOCATION:</b>	Dry
<b>CUT OUT HOLE:</b>	L: 110mm W: 35mm L: 4.33" W: 1.38"	<b>FITTING METHOD:</b>	Included Junction Box
<b>RECESS DEPTH:</b>	90mm/3.54"	<b>ADA COMPLIANT:</b>	To Be Advised
<b>FIRE RATING:</b>	Not Applicable	<b>IC RATING:</b>	IC Rated
		<b>VOLTAGE:</b>	Mains 120V


LAMP

<b>LIGHT SOURCE:</b>	High Power LED	<b>MACADAM ELIPSE:</b>	3-Step
<b>MAXIMUM WATTAGE:</b>	1W	<b>UGR:</b>	Not Applicable
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	20.8 (Degrees)
<b>LAMP INCLUDED?</b>	Yes (Integral)	<b>TILT ADJUSTMENT ANGLE:</b>	180 (Degrees)
<b>DELIVERED LUMENS:</b>	61.13 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	180 (Degrees)
<b>COLOR TEMP:</b>	2700 (K)	<b>AVERAGE LIFESPAN:</b>	To Be Advised
<b>CRI:</b>	80	<b>L70:</b>	To Be Advised
<b>R9:</b>	22.2		

ELECTRICAL

<b>SWITCHED:</b>	Yes	<b>SUPPLY FREQUENCY:</b>	50 / 60 (Hz)
<b>DIMMABLE:</b>	No	<b>DRIVER/BALLAST VOLTAGE:</b>	100 - 240 (V)
<b>DIMMING METHOD:</b>	Not Applicable	<b>DRIVER AVERAGE LIFESPAN:</b>	60,000 (hrs)
<b>DRIVER OUTPUT CURRENT:</b>	350 (mA)	<b>EFFICACY:</b>	26.01 (lm/w)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER/BALLAST INCLUDED?</b>	Yes (Integral)

ADDITIONAL INFORMATION



BOX QUANTITY X 6

# PRODUCT ELEVATIONS

---

