

# ENNA SURFACE 7356

SKU 1058012

astro



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                           |                       |           |
|----------------------------------|---------------------------|-----------------------|-----------|
| <b>FINISH:</b>                   | Bronze                    | <b>GROSS WEIGHT:</b>  | 0.6000 kg |
| <b>MAIN MATERIAL:</b>            | Aluminium                 | <b>CLASS:</b>         | 1         |
| <b>DIMENSIONS:</b>               | H: 110mm W: 155mm D: 80mm | <b>IP RATING:</b>     | IP20      |
| <b>INSTALLATION ORIENTATION:</b> | Wall Mount - Vertical     | <b>BATHROOM ZONE:</b> | 3         |
| <b>CUT OUT HOLE:</b>             | Not applicable            | <b>VOLTAGE:</b>       | 230V      |
| <b>CABLE LENGTH:</b>             | Not applicable            |                       |           |


### LAMP

|                             |                |                                   |                |
|-----------------------------|----------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | LED            | <b>R9:</b>                        | To be advised  |
| <b>MAXIMUM WATTAGE:</b>     | 3W             | <b>UGR:</b>                       | Not applicable |
| <b>MAXIMUM LAMP LENGTH:</b> | Not applicable | <b>BEAM ANGLE:</b>                | 45°            |
| <b>LAMP INCLUDED:</b>       | Included       | <b>TILT ADJUSTMENT ANGLE:</b>     | 90°            |
| <b>LUMINOUS FLUX:</b>       | 95 lm          | <b>ROTATION ADJUSTMENT ANGLE:</b> | 330°           |
| <b>COLOUR TEMP:</b>         | 2700K          | <b>AVERAGE LIFESPAN:</b>          | 54,000 hrs     |
| <b>CRI:</b>                 | 80             |                                   |                |

### ELECTRICAL

|                          |                       |                                 |                 |
|--------------------------|-----------------------|---------------------------------|-----------------|
| <b>SWITCHED:</b>         | Yes                   | <b>DRIVER/BALLAST VOLTAGE:</b>  | 100-240V        |
| <b>DIMMABLE:</b>         | No                    | <b>DRIVER AVERAGE LIFESPAN:</b> | 60,000 hrs      |
| <b>DIMMING METHOD:</b>   | Not applicable        | <b>L70:</b>                     | 30,000 hrs      |
| <b>DRIVER:</b>           | 700mA Driver Included | <b>EFFICACY (lm/w):</b>         | To be confirmed |
| <b>SUPPLY FREQUENCY:</b> | 50/60 Hz              |                                 |                 |

## ADDITIONAL INFORMATION



BOX QUANTITY X12

# PRODUCT ELEVATIONS

---

