

MAYFAIR ADJUSTABLE 5744

SKU 1377002

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	White	CABLE LENGTH:	0.45 (mm)
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.32 (kg)
DIMENSIONS:	DIA: 87mm D: 94mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Ceiling Mount	IP RATING:	IP65
CUT OUT HOLE:	73mm/2-7/8"	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	114 (mm)	VOLTAGE:	Constant Current 700 (mA)
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Not suitable for covering with thermal insulation

LAMP

LIGHT SOURCE:	COB LED	MACADAM ELIPSE:	3-Step
MAXIMUM WATTAGE:	6.8W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	25 (Degrees)
LAMP INCLUDED?	Yes	TILT ADJUSTMENT ANGLE:	45 (Degrees)
LUMINOUS FLUX:	332.07 (lm)	ROTATION ADJUSTMENT ANGLE:	360 (Degrees)
COLOUR TEMP:	2700 (K)	AVERAGE LIFESPAN:	36,300 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	6.0		


ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER/BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Control Gear Dependant	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	38.17 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	No

ADDITIONAL INFORMATION



Product tested with 1836 - LED Driver CC 250/350/500/700mA DALI Dim



BOX QUANTITY x 20

PRODUCT ELEVATIONS



73mm/2-7/8"

