



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Polished Chrome	<b>GROSS WEIGHT:</b>	4.63 (lbs)
<b>MAIN MATERIAL:</b>	Metal - Mild Steel	<b>CLASS:</b>	cETLus (Class I)
<b>DIMENSIONS:</b>	H:600mm W:100mm D: 75mm H:23.62" W3.93" D: 2.95"	<b>LISTING LOCATION:</b>	Damp
<b>INSTALLATION ORIENTATION:</b>	Wall Mount - Vertical / Horizontal	<b>FITTING METHOD:</b>	1/2 Stub Mount 4" Octagon box
<b>CUT OUT HOLE:</b>	Not Applicable	<b>ADA COMPLIANT:</b>	Yes
<b>RECESS DEPTH:</b>	Not Applicable	<b>IC RATING:</b>	Not Applicable
<b>FIRE RATING:</b>	Not Applicable	<b>VOLTAGE:</b>	Mains 120 (V)
<b>CABLE LENGTH:</b>	Not Applicable		

### LAMP

<b>LIGHT SOURCE:</b>	T5 HO	<b>MACADAM ELIPSE:</b>	Not Applicable
<b>MAXIMUM WATTAGE:</b>	1 x 24W	<b>UGR:</b>	Not Applicable
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	113.4 (Degrees)
<b>LAMP INCLUDED?</b>	No	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>DELIVERED LUMENS:</b>	629 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOR TEMP:</b>	Lamp dependant	<b>AVERAGE LIFESPAN:</b>	19,000 (Hrs)
<b>CRI:</b>	80	<b>L70:</b>	Not Applicable
<b>R9:</b>	-12.9		


### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	50/60 (Hz)
<b>DIMMABLE:</b>	No	<b>DRIVER / BALLAST VOLTAGE:</b>	120 (V)
<b>DIMMING METHOD:</b>	Not Applicable	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	31.83 (lm/w)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER INCLUDED?</b>	Yes (Integral)

## ADDITIONAL INFORMATION



This product is not suitable for use with a PIR motion detector.



BOX QUANTITY X6

# PRODUCT ELEVATIONS

