

Employ greater flexibility in commercial design with Autex's Workstation; a Veriface® covered polyester panel that combines superior noise absorption with unique finishing options.

Durable and lightweight, Workstation can be used in wide array of commercial applications, including office dividers and partitions, sustainable furniture and as a creative medium for sound absorbing feature pieces. Workstation will help increase privacy in open offices, reduce reverberated sound and assist in controlling background chatter noise; creating a private, comfortable and functioning workplace environment.

With the ability to custom print and cut, the bright and clean colours of Workstation can inspire unique designs and creative solutions where functionality and aesthetics are crucial.

Made from 100% recyclable polyester and manufactured under Autex's ISO 9001 and ISO 14001 accredited Quality and Environmental Management Systems, Workstation products contain a minimum of 60% post-consumer recycled material (PET bottle-flake). Completely non-toxic, non-allergenic and non-irritant, Workstation is the safe, low VOC solution to redefining your office environment.

Key Features and Benefits

- Design flexibility with custom cutting and printing
- Excellent acoustic performance
- Available in a range of sophisticated colours with single and double-sided colour options
- Option to have different colours each side of the panel
- Light-weight and easy to handle
- Made from 100% polyester fibre without chemical binders and certified low VOC
- Manufactured using a minimum of 60% post-consumer recycled material
- Highly durable providing long-term stability and performance
- Safe, non-toxic, non-irritant and non-allergenic
- Made in New Zealand and Australia

- Manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems
- Does not contain any Red List chemicals *

Applications

- Decorative and functional acoustic wallcovering for education, retail and commercial interiors
- Base material for office privacy screens
- Media for creative solutions
- Acoustic pinboard surface for the education and commercial sectors
- Modular room divider for display, privacy and sound absorption
- Free-standing or direct fix acoustic panel

Colour Options

Workstation is available in a range of sophisticated colours to suit many different environments.

Refer to the Workstation Colour Guide available on the Autex website or from your Account Manager.

Custom Design Options

Push the limitless design flexibility of Workstation and take your ideas to the next level.

Combining our specialised custom cutting and printing services with Workstation, you can immortalise your design or logo and create unique brand awareness.

* Green Building Rating Compatibility certificate can be found on www.envirospec.co.nz or from your Autex Account Manager

Specification:

(Wall) (Partition) treatment shall be **Autex Workstation** from thermally bonded polyester containing not less than 60% post-consumer recycled material as manufactured by Autex www.autexindustries.com

Panel 1200 x 2400 x (L)mm (nom.) depth, colour (L), sound absorption 6mm: Class E, NRC 0.20 – with 24mm air gap: Class D, NRC 0.50. 12mm: Class D, NRC 0.45 – with 24mm air gap: Class C, NRC 0.70. Fire rating: ISO 9705: Classification: Group 1-S, AS ISO 9705 – 2003: Group 1, EN13501-1:2007+A1:2009: Classification: B - s1, d2

Install as per Autex recommendations. If Workstation is to be specified for use other than as a wallcovering or partition, please seek guidance from your Autex Account Manager.

Product Specifications

Product Name	Workstation	
Composition	100% Polyester Fibre (PET)	
Panel Dimensions	1205mm (+/- 5mm)	x 2410mm (+/- 10mm)
Thickness	6mm	12mm
Weight	1200gsm	2400gsm
Density	200kg/m ³	

Installation

Install as per Autex recommendations.

Fastness to Light

Workstation is suitable for indoor use only. Custom printed Workstation can be offered with UV resistance on request. Please discuss your requirements with your Autex Account Manager.

Autex Veriface[®] fabric has been tested to the following standard:

ISO105-B02-1994 (Grey Scale 1-5)

Light Fastness Rating: 3

Fire Ratings (Conducted on 6mm Workstation)

ISO 9705: 1993

Classification: Group 1-S

Smoke Production Rate: <5.0m²/s

As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1

(SMOGR_{ARC}): <100m²/s²

As required by BCA C1.10

Fl 4974 dated 16th September, 2012

EN13501-1:2007+A1:2009

B - s1, d2

Report WF 336913 dated 19th March, 2014

VOC Emissions

Autex polyester has been tested by Cetec Pty Ltd (Report: CV080408) for chemical emission and is classified as low VOC.

VOC concentration: 0.01 mg/m³

Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture, mould or mildew and will not rot or deteriorate in intended use situations.

Fabric Care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution.


Custom printed Workstation requires the services of a specialist cleaning company.

Acoustic Performance

Workstation is specifically designed to reduce and control reverberated (echo) noise in building interiors.

Minimum Noise Reduction Coefficient (NRC) 0.20

Sound Absorption Coefficient according to ISO 354. University of Auckland Testing Service
Workstation 6mm - Test No. T0712
Workstation 12mm - Test No. T07123



Frequency (Hz)	125	250	500	1000	2000	4000	NRC
6mm Workstation	0.00	0.02	0.07	0.20	0.46	0.71	0.20
6mm Workstation (with 25mm air gap)	0.05	0.13	0.33	0.69	0.94	0.88	0.50
12mm Workstation	0.00	0.08	0.28	0.64	0.89	0.96	0.45
12mm Workstation (with 25mm air gap)	0.05	0.27	0.61	0.94	0.97	0.85	0.70

Pattern Repeat

Non-woven. No pattern repeat but product has directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up which is an inherent feature of this product.

Impact Resistance

Workstation has been tested for impact resistance to EN13964:2004 and meets the criteria of Class 1A; not adversely affected at impact velocities over 16.5m/s.

Environmental

Autex is committed to best practice through our ISO 9001 and ISO 14001 accredited Quality and Environmental Management Systems.

Workstation products contains a minimum of 60% previously recycled polyester fibre (from PET bottle-flake) ensuring comparatively low embodied energy. Off-cuts and manufacturing waste is re-used or recycled wherever possible.

Workstation is manufactured from 100% polyester fibres and does not contain formaldehyde binders. Autex polyester fibres support safer indoor air quality and will not become a potential airborne pollutant.

Service

For further information about Workstation or any other Autex product, please contact your Autex Account Manager or visit our website.

Autex Workstation is proudly manufactured in New Zealand by Autex Industries Ltd and in Australia by Autex Pty Ltd.