



### **The AUTOPA Fixed Post 750**

The galvanised mild steel range of 750mm tall fixed posts are suitable for a range of applications and are ideal as a complement to the Autopa ranges of Parking Posts, RemovaPosts and RetractaPosts. The round posts are available in 60mm, 76mm, 90mm, 101mm, 114mm, 139mm and 168mm diameter tube. The Fixed Post is available with a Ragged finish (for casting into new concrete) or Flanged (for bolting to existing concrete).

The Fixed Post 750 is finished with a welded steel cap.

The AUTOPA Fixed Post is shown in 90mm with Flanged fixing.

### **Product Range**

| <b>Order Code</b> | <b>Description</b> | <b>Weight</b> |
|-------------------|--------------------|---------------|
| 138 121 101       | 60mm (Ragged)      | 4.4kg         |
| 138 121 102       | 60mm (Flanged)     | 3.8kg         |
| 138 121 253       | 76mm (Ragged)      | 5.7kg         |
| 138 121 283       | 90mm (Ragged)      | 6.7kg         |
| 138 121 278       | 90mm (Flanged)     | 5.7kg         |
| 138 121 323       | 101mm (Ragged)     | 7.7kg         |
| 138 121 326       | 101mm (Flanged)    | 7.0kg         |
| 138 121 423       | 114mm (Ragged)     | 8.7kg         |
| 138 121 424       | 114mm (Flanged)    | 7.8kg         |
| 138 121 623       | 139mm (Ragged)     | 17.0kg        |
| 138 121 723       | 168mm (Ragged)     | 20.9kg        |

#### **Accessories & installation parts**

|           |                                    |
|-----------|------------------------------------|
| 138100994 | M12 Expanding Bolt (Flanged only)  |
| 138100993 | M12 Foundation Bolt (Flanged only) |
| 138100995 | M12 Rawl Bolt (Flanged only)       |

#### **Product details**

750mm Tall.  
Ragged Posts 250mm below ground.  
Welded steel cap.  
Galvanised steel finish.

#### **Installation & use**

Flanged fixed posts require bolting down to a suitable concrete surface (no less than 300mm cube) by means of three/four M12 bolts.  
Ragged fixed posts are supplied with welded fixing spikes to ensure firm ground anchorage.  
Ragged posts require a hole of at least 300mm deep for casting into concrete.  
This product is guaranteed for 12 months (*if installed and used correctly*).

[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

