

## TECHNICAL DATA SHEET

### Bauder AP2 Capping Sheet

#### DESCRIPTION

A top quality, heavy duty, torch-applied, elastomeric bitumen capping sheet. The product features chemically treated bitumen to deliver superior root resistance which has been tested and approved by the FLL. The membrane is reinforced with 250g/m<sup>2</sup> spunbond polyester fleece to allow the finished product to cope with structural movement without fracture.

#### TECHNICAL DATA:

##### Weights and sizes

Roll width	1 metre
Roll length	7.5 metres
Thickness:	4.2mm
Weight:	5kg/m <sup>2</sup>
Reinforcement:	250g/m <sup>2</sup> spunbond polyester

##### Surface finishes

Top:	green slate mineral chippings
Bottom:	foil

##### Technical performance

Tensile strength:	length	≥ 1000N/50mm
	diagonal	≥ 1000N/50mm

Elasticity at fracture of reinforcement:	length	≥ 45%
	diagonal	≥ 45%

Cold bending test:	-36°C
Softening point:	+120°C



#### UNITED KINGDOM

##### Bauder Ltd

70 Landseer Road  
Ipswich Suffolk England IP3 0DH  
**T:** +44 (0)1473 257671 **E:** info@bauder.co.uk  
[bauder.co.uk](http://bauder.co.uk)

#### IRELAND

##### Bauder Ltd

O'Duffy Centre Cross Lane Carrickmacross  
Co. Monaghan Ireland  
**T:** +353 (0)42 9692 333 **E:** info@bauder.ie  
[bauder.ie](http://bauder.ie)