

TECHNICAL DATA SHEET

Bauder K5E Capping Sheet

DESCRIPTION

A top quality, heavy duty, torch-applied elastomeric bitumen capping sheet. The product features a spunbond polyester reinforcement to allow the finished product to cope with structural movement without fracture. It's mica finish means that it has no integrated UV protection, therefore only suitable for applications where it will be covered with hard landscaping such as pavers, promenade tiles or timber decking.

TECHNICAL DATA:

Weights and sizes

Roll width	1 metre
Roll length	5 metres
Thickness:	5mm
Weight:	5.8Kg/m ²
Reinforcement:	250g/m ² spunbond polyester

Surface finishes

Top:	mica
Bottom:	foil

Technical performance

Tensile strength:	≥ 800N/50mm
Elasticity at fracture of re-inforcement:	≥ 40%
Cold bending test:	-30°C
Softening point:	+110°C



UNITED KINGDOM

Bauder Ltd

70 Landseer Road
Ipswich Suffolk England IP3 0DH
T: +44 (0)1473 257671 **E:** info@bauder.co.uk
bauder.co.uk

IRELAND

Bauder Ltd

O'Duffy Centre Cross Lane Carrickmacross
Co. Monaghan Ireland
T: +353 (0)42 9692 333 **E:** info@bauder.ie
bauder.ie