

# XACARA-L INDIRECT

WEB PIN™ 167



## GENERAL SPECIFICATION

**Body:** Die cast aluminum and steel.

**Finish:** White powder coated.

**Suspension:** Two polished chrome plated tubes or three stainless steel aircraft cables.

**Visible power cable:** Silver braided.

**Reflectors:** Aluminum, specular finish with vertical facets.

**LED array protection:** Integrated clear lenses.

**Dust cover:** Clear polycarbonate.

**Drivers:** HPF electronic 120-277V, 0-10V dimming.

**Mechanical:** Luminaires mount directly over a junction box (not supplied).

**Approvals:** ETL/US, ETL/C, CE.

## INDIRECT ILLUMINATION PENDANT

### A SPECIFY LAMP TYPE

Code:	Lamp:	CCT:	CRI:	Delivered lms:	Efficacy LPW:	Photometry:
50 3520	5 x 26W LED	3000K	80	8726	65.1	File# 503520
50 3521	5 x 26W LED	3000K	90	7600	56.7	File# 503521
50 3522	5 x 26W LED	3500K	80	9350	69.8	File# 503522
50 3523	5 x 26W LED	4000K	80	9850	73.5	File# 503523
50 3620	6 x 26W LED	3000K	80	10450	65.0	File# 503620
50 3621	6 x 26W LED	3000K	90	9100	56.5	File# 503621
50 3622	6 x 26W LED	3500K	80	11200	69.6	File# 503622
50 3623	6 x 26W LED	4000K	80	11800	73.3	File# 503623

### B SPECIFY SUSPENSION

- TS Tube suspension
- CS Cable suspension (6 lamp only)

### C SPECIFY OPTIONS

- DC Dust cover (clear acrylic)
- CT Custom tube length (contact factory)
- 3 347V (5 lamp only)

Example Specification Code: 50 3520 - TS

Photometric testing performed using LM79 procedures.

