

BARRIER TECH CATCH & BARRIER TECH STEP UP

PRODUCT SPECIFICATION

	BARRIER TECH CATCH	BARRIER TECH STEP UP TILES
Pile Yarn	PVC/PP	6.6 Nylon with 6.6 scraper yarn
Construction	Loop Pile Graphics	Cut & Loop Pile Graphics
Primary Backing	Colbac	Colbac
Secondary Backing	Vinyl	PVC Mix
Pile Weight	+/- 950 gms/m ²	+/- 1288 gms/m ²
Total Weight	+/- 4000 gms/m ²	+/- 6390 gms/m ²
Pile Height	+/- 7mm	+/- 3.3mm
Total Thickness	11mm nominal	9.5mm nominal
Gauge	1/8th	5/32"
Standard Roll/Tiles	20m x 2.05m (approx)	60.90cm x 60.90cm

All sizes on broadloom include borders. 40.4% pre-consumer recycled content of total weight in tiles.

TECHNICAL SPECIFICATION

Performance Rating	Heavy Contract
Flammability BS4790: 1987 (1996)	Hot Metal Nut Test Pass
Static Electricity	Stroll Test - Less than 3.0kV
Castor Chair Rating	Pass
Tuft Anchorage	Greater than 3.5kg

INSTALLATION

All carpets should be fitted in accordance with **BS 5325: 1996**.

Recommended adhesives for Broadloom:

For Permanent Bonding	Styccobond F45
For Wet Areas Broadloom	Styccobond F74/F81

SEAMS MUST BE SEALED WITH A SEAM SEALING ADHESIVE

Recommended adhesives for Carpet Tiles:

For Permanent Bonding	Styccobond F45
For Release Bonding	Styccobond F41

MAINTENANCE

Barrier Tech Catch and Barrier Tech Step Up should be vacuumed regularly, commercial cleaning using the "Envirodry System" or the **Hot Water Extraction** method is recommended depending on conditions. Spot clean immediately on spill. For further advice on maintenance contact Simon Dickinson on 0115 989 9210.

5 Year Limited Wear Warranty Contact the office for details.



Birch Carpets

Hazel Park Mills, 318 Coleford Road, Sheffield, S9 5PH

Tel 0114 243 1230

Fax 0114 243 5118

Email info@birchcarpets.co.uk

www.birchcarpets.co.uk



Birch Carpets
MANUFACTURING INSPIRATION

All specifications +/- are within 10% of specification.
Birch Carpets reserve the right to change or modify specifications without giving prior notice.