

CARE TECH & CARE TECH PLAIN

Product Specification	CARE TECH	CARE TECH PLAIN
Pile Yarn	100% Meraklon PP	100% Meraklon PP
Construction	2 Ply Twist Cut Pile	2 Ply Twist Cut Pile
Backing	Impervious Foam	Impervious Foam
Pile Weight	1200g/m ²	1100g/m ²
Total Weight	2100/m ²	2000/m ²
Pile Height	6mm	6mm
Gauge	1/10 th	1/10 th
Number of Tufts	160,000/m ²	160,000/m ²
Standard Roll	25m x 4m (approx)	25m x 4m (approx)
Colour Range	21	10

Technical Specification – Overall Performance Rating

Flammability Classification	BS4790 Low Radius of Effects of Ignition
Electrostatic Properties	Walking Test <2.0KV Resistance $\geq 10^{10}$
Suitability	BS7131 (1) Heavy Contract
Impact Sound Reduction	29dB (A) Foam Back
Bleach Resistance	Yes
Colour Fastness to Light	≥ 7 according to ISO 105-B02
Colour Fastness to Rubbing	$\geq 3 - 4$ according to ISO 105-X12
Special Stain Resistant Treatment	Yes
Anti-Bacterial Treatment	Yes
Anti-Fungi Treatment	Yes
Anti-Mould Treatment	Yes
Anti-Mildew Treatment	Yes
Anti-Dust Mites Treatment	Yes
Suitable for Alzheimer's Patient Care Areas	Yes
Ultra Fresh	Yes

COMBATS MRSA & E.COLI & OTHER MICRO ORGANISMS

Installation

All carpets should be fitted in accordance with BS5325: 1996.
Adequate protection should be allowed under roller castor chairs.

Recommended adhesives:

For Permanent Bonding:.....Styccobond F3
For Vertical Bonding:.....Styccobond F60

SEAMS MUST BE SEALED WITH SEAM SEALING ADHESIVE.

Maintenance

Care Tech® and Care Tech Plain® should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction' method is recommended depending on conditions.

Spot clean immediately on spill.

For further advice on maintenance, contact Simon Dickinson on 0115 989 9210.

10 Year Limited Wear Warranty - Contact the office for details.



Birch Carpets
Hazel Park Mills
318 Coleford Road
Sheffield
S9 5PH
Tel 0114 243 1230
Fax 0114 243 5118
Email info@birchcarpets.co.uk
Website www.birchcarpets.co.uk

