

MED TECH

PRODUCT SPECIFICATION

Product method	Tufted 1/8" gauge
Surface structure	coc/Hard twist
Pile material	100% Meraklon polypropylene
Pile height	8mm nominal
Total thickness	10mm nominal
Pile weight.....	1100 g/m ²
Total weight.....	2800 g/m ² Impervious foam back
Number of tufts.....	155,000m ²
Primary backing.....	100% polypropylene
Backing	Impervious foam
Standard roll.....	30m x 4m (approx)

TECHNICAL SPECIFICATION

Contract rating	Heavy contract
Flammability	BS 4790 Hot metal nut test
Thermal conductivity	15kW/m ²
Impact sound reduction	29 DB(A) foam back
Gut-test number.....	17784

INSTALLATION

All carpets should be fitted in accordance with **BS 5325: 1996**.
Adequate protection should be allowed under roller castor chairs.

Recommended adhesives:

For Permanent Bonding

Styccobond F3

For Vertical Bonding

Styccobond F60

SEAMS MUST BE SEALED WITH SEAM SEALING ADHESIVE

Maintenance:

Med Tech® should be vacuumed regularly, commercial cleaning using the "Host Dry Cleaning System" or the Hot Water Extraction method is recommended depending on conditions.

Guarantee: 7 years stain removal warranty; 7 years wear warranty



Birch International Carpets

Hazel Park Mills, 318 Coleford Road, Sheffield S9 5PH

Tel: 0114 243 1230

Fax: 0114 243 5118

info@birchinternational.co.uk

www.birchinternational.co.uk

