

 bradbury	M2M ³ M2M ³ FD	M2M ² M2M ² FD	M2M ¹ M2M ¹ FD	M2M ⁺ M2M ⁺ FD	SPECIALIST / SPECIALIST ^{FD}
					
Certification and Testing	   Bradbury Security M2M ³ Assessed to LPS1175: Issue 7 Cert No. 312e Security Rating 3	   Bradbury Security M2M ² Assessed to LPS1175: Issue 7 Cert No. 312f Security Rating 2	  Bradbury Security M2M ¹ Assessed to LPS1175: Issue 6 Cert No. 312d Security Rating 1		
	Approved by the Association of British Insurers	Approved by the Association of British Insurers	Approved by the Association of British Insurers		
Security Rating	Certified to LPS1175 (Issue 7) Security Rating 3 Issued 2011	Certified to LPS1175 (Issue 7) Security Rating 2 Issued 2013	Certified to LPS1175 (Issue 6) Security Rating 1 Issued 2008		
Fire Rating	EN1634-1/BS476: Part 22 1987 CF5107 - Up to 240 minutes	EN1634-1/BS476: Part 22 1987 CF5107 - Up to 240 minutes	EN1634-1/BS476: Part 22 1987 CF5108 - Up to 240 minutes	EN1634-1/BS476: Part 22 1987 CF5108 - Up to 240 minutes	EN1634-1/BS476: Part 22 1987 CF5108 - Up to 240 minutes
Features and Applications	The M2M ³ range offers an unrivalled selection of certified high security single and double doors suitable for all personnel, fire exit, access control and utility applications. The range has been Certified to LPS1175 (Issue 7), and the wide choice of hardware options allows the doors to be tailor made to individual customer requirements.	The M2M ² range is developed from Bradbury's successful M2M ³ range. Offering the most popular hardware options, it combines a lightweight design with the confidence of an LPS 1175 Security Rating.	Our M2M ¹ door is an outward opening single door design, featuring many aspects of our M2M ⁺ doors with the added advantage of third party testing. The doors feature localised reinforcing and are available with a selective range of locking options.	Our best-selling range of doors, the M2M ⁺ is a general purpose steel door with an extensive selection of extras to ensure that each door can be adapted to suit your individual needs. These attractive doors are suitable for a wide range of uses, from commercial to industrial and even domestic.	Bradbury's in-house technical team may be able to engineer tailored solutions if there is specific hardware to be included in the door; contact our sales team to find out more. Please note, a specialist charge starts from £62 per door, depending on the modification required.
Glazing	Yes	Yes	No	Yes	Yes
Louvres	Yes (not M2M ³ FD)	Yes (not M2M ² FD)	No	Yes	Yes
Opening	Outward & Inward*	Outward & Inward*	Outward	Outward & Inward	Outward & Inward
Panels	Fixed and removable overpanels Fixed side panels	Fixed and removable overpanels Fixed side panels	N/A	Fixed and removable overpanels Fixed side panels	Fixed and removable overpanels Fixed side panels
Download	M2M3 SPECIFICATION	M2M2 SPECIFICATION	M2M1 SPECIFICATION	M2M+ SPECIFICATION	

	 SECURITY RATING 3	 SECURITY RATING 2	 SECURITY RATING 1
TESTING TOOLS INCLUDE	• SR 1 & 2 TOOL PLUS • AXE • CAR JACK • COLD CHISEL • GAS TORCH • CORDLESS DRILL	• SR 1 TOOL PLUS • BOLT CUTTER • CLAW HAMMER • HACKSAW • HAND DRILL • PIPE WRENCH	• PRY BARS • SCREWDRIVER • WRENCH KNIFE • GLASS CUTTER • KNIFE • PLIERS
	MAXIMUM TEST DURATION 20 MINUTES	MAXIMUM TEST DURATION 15 MINUTES	MAXIMUM TEST DURATION 10 MINUTES
	MAXIMUM WORKING TIME 5 MINUTES	MAXIMUM WORKING TIME 3 MINUTES	MAXIMUM WORKING TIME 1 MINUTE

* Pending certification by the LPCB