



The National BIM Library

BIM Object Guide: RESITRIX® SR



Version 2.0

22nd May 2014

www.nationalBIMlibrary.com

Contents

1.0 Introduction	3
1.1 Naming.....	3
2.0 Parameters	5
2.1 National BIM Library Parameters.....	5
2.2 NBS Parameters.....	5
2.3 Manufacturers Parameters	5
2.4 IFC Parameters	6
2.5 COBie Parameters	8
3.0 Abbreviations	10

1.0 Introduction

This guide covers the use of RESITRIX® SR included within the National BIM Library.

RESITRIX® SR



All products listed below are included in the following file:

nbl_PolymericRoofingMembranes_PDTSealingSystemsLtd_RESITRIXSR

RESITRIX® SR

1.1 Naming

National BIM Library objects are named to identify their type and configuration. Fields are segregated using an under bar (_) and information within each field is segregated using hyphens (-). Fields are abbreviated to reduce characters and capitals used at the start of each abbreviation to aid readability.

File name and objects are named as below:

File name

Field1 *Author_***Field2** *Category_***Field3** *Manufacturer_***Field4** *Product Range*

Object

Field1 *Author_***Field2** *Category***Field3** *Manufacturer_***Field4** *Product_***Field5** *Differentiator*

2.0 Parameters

Parameters included in the RESITRIX® SR BIM object are as follows:

2.1 National BIM Library Parameters

Author	The name of the BIM objects Author.
BIMObjectName	Name of the BIM object as it will appear in software. Using NBL naming procedure.
Description	The full description of a product or system.
Help	URL of a website where additional help notes are available.
IssueDate	The issue date of this BIM object.
ManufacturerURL	URL of the product or system manufacturer.
NBSDescription	NBS Uniclass title.
NBSNote	Where a second system which is related to the BIM object can be described.
NBSReference	NBS Uniclass section/clause number.
NBSTypeID	A reference to the object for the user if one or more is used within the project.
Uniclass2	Uniclass2 code.
Version	The version number of the BIM object.

2.2 NBS Parameters

Certification	Product approval and certification by an accredited organisation.
IntegralBackingFleece	Material used for backing fleece if required. If not please state None.

2.3 Manufacturers Parameters

BottomSurface	Description of the bottom surface of the membrane.
ColdBendingTest	A description of how the product performs to BS EN 1109. Flexible sheets for waterproofing. Bitumen sheets for roof waterproofing. Determination of flexibility at low temperature.
DimensionalStability	A description of how the product performs to BS EN 1107-2. Flexible sheets for waterproofing. Determination of dimensional stability. Plastic and rubber sheets for roof waterproofing.
ElongationAtBreak	A description of how the product performs to BS EN 12311-2. Flexible sheets for waterproofing. Determination of tensile properties. Plastic and rubber sheets for roof waterproofing.
FixingOptions	A list of options of which fixings should be used for the related product.
JointPeelResistance	A description of how the product performs to BS EN 12316-2. Flexible sheets for waterproofing. Determination of peel resistance of joints. Plastic and rubber sheets for roof waterproofing.
JointShearResistance	A description of how the product performs to BS EN 12317-2. Flexible sheets for waterproofing. Determination of shear resistance of joints. Plastic and rubber sheets for roof waterproofing.
MassPerUnitArea	Determination of thickness and mass per unit area to BS EN 1849-2.
OzoneResistance	A description of how the product performs to BS EN 1844. Flexible sheets for waterproofing. Determination of resistance to ozone. Plastic and rubber sheets for roof waterproofing.
RollLength	Standard roll length measured in [m].
RollWidth	Standard roll width measured in [m].
TensileStrength	A description of how the product performs to BS EN 12311-2. Flexible sheets for waterproofing. Determination of tensile properties. Plastic and rubber sheets for roof waterproofing.

2.4 IFC Parameters

Note: IFC definitions have been obtained from BuildingSmart IFC2x3 website (<http://buildingsmart-tech.org>).

AcousticRating	Acoustic rating for this object. It is given according to the national building code. It indicates the sound transmission resistance of this object by an index rating (instead of providing full sound absorption values).
Combustible	Indication whether the object is made from combustible material (TRUE) or not (FALSE).
FireRating	Fire rating for this object. It is given according to the national fire safety classification.
Finish	Finish selection for this object. Here specification of the surface finish for informational purposes.
FlammabilityRating	Flammability Rating for this object. It is given according to the national building code that governs the rating of flammability for materials.
FragilityRating	Flammability Rating for this object. It is given according to the national building code that governs the rating of flammability for materials.
Material	Main material of the covering, it should only be given, if no IfcMaterial class is assigned to the IfcCovering instance.
Reference	Reference ID for this specified type in this project (e.g. type A-1).
SurfaceSpreadOfFlame	Indication on how the flames spread around the surface, It is given according to the national building code that governs the fire behaviour for materials.
TotalThickness	Thickness of the covering, The thickness information is provided in addition to the shape representation and the geometric parameters used within. In cases of inconsistency between the geometric parameters and the shape properties, provided in the attached property, the geometric parameters take precedence.

2.5 COBie Parameters

The following COBie parameters have been included within the RESITRIX® SR BIM object and can be used to prepare COBie data schedules:

AccessibilityPerformance	Accessibility issue(s) which the product satisfies.
AssetIdentifier	The asset identifier assigned to an occurrence of a product (prior to handover).
BarCode	The identity of the bar code (or rfid) given to an occurrence of the product.
CodePerformance	Code Compliance requirement(s) which the product satisfies.
Colour	Characteristic or primary colour of product.
Constituents	Optional constituent features, parts or finishes.
Cost	Cost impact of replacement process.
Documentation	Location (Uniform Resource Information) for further product information.
DocumentReference	Location (Uniform Resource Information) for the source or updates to this product information.
Features	Features or other important characteristics relevant to product specification.
Grade	Standard grading(s) to which the product corresponds.
InstallationDate	The date that the manufactured item was installed.
LifeCyclePhase	Life Cycle Phase as defined in ISO 15978.
Manufacturer	The organization that manufactured or assembled the item.
MethodOfMeasurement	Method of measurement.
ModelLabel	The model number assigned by manufacturer.
ModelReference	The name used by the manufacturer.

NominalHeight	Nominal height of product, typically the vertical or secondary characteristic dimension.
NominalLength	Nominal length of product, typically the larger or primary horizontal dimension.
NominalWidth	Nominal width of product, typically the characteristic or secondary horizontal or characteristic dimension.
Process	Specification of process.
ProductionYear	The year of production for the manufactured item.
ReferenceStandard	Reference standard(s) to which the product is compliant.
ReplacementCost	An indicative cost for unit replacement.
SerialNumber	The serial number assigned to an occurrence of a product by the manufacturer.
ServiceLifeDuration	The length or duration of a service life.
ServiceLifeType	The typical service life that is quoted for an artefact under reference operating conditions.
Shape	Characteristic shape of product.
Size	Characteristic size of product.
SustainabilityPerformance	Sustainability issue(s) which the product satisfies.
TagNumber	The tag number assigned to an occurrence of a product.
WarrantyDescription	Description of the warranty.
WarrantyDurationLabour	Duration of labour warranty (years).
WarrantyDurationParts	Duration of parts warranty (years).
WarrantyGuarantorLabour	Organization acting as guarantor of labour warranty.
WarrantyGuarantorParts	Organization acting as guarantor of parts warranty.
WarrantyStartDate	The date on which the warranty commences.

3.0 Abbreviations

nbl national BIM library