

# SECURE

PRODUCT DATASHEET



## INDEPENDENTLY CERTIFIED SECURITY SYSTEM



### ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8 Security Rating A1
- Secured By Design Police Preferred Specification



### STACK TECHNOLOGY

- More than 80% free airflow
- Small stacking zone at high level
- Self-locking to prevent lifting with no auxiliary locks



### TYPICAL APPLICATIONS

- Multi-use car parks
- High risk retail buildings
- Vandal resistant applications




### OPTIONS

- Stainless Steel or Polyester powder coated to any standard RAL/BS colour
- High or low duty cycle electrical motors
- Integration with third party controls



Stackdoor Shutters are manufactured in the UK by CGT Security.



 INDEPENDENTLY CERTIFIED SECURITY SYSTEM

## PRODUCT REFERENCE

Stackdoor Secure

Certified to LPS 1175 Issue 8 Security Rating A1

## SHUTTER CURTAIN

Stainless or zinc plated steel pins secured into horizontal stainless, zinc plated or powder coated steel profiles

## APPROVED DIMENSIONS

Minimum width: 1000mm

Maximum width: 6000mm

Minimum height: 2000mm

Maximum height: 10000mm

## OPERATION

Motorised to allow controlled ascent and descent

Tube Motor - Low duty cycle, for application up to 4 cycles per day

External Drive Motor - High duty cycle for heavy use applications and/or larger apertures

## BOTTOM RAIL & FRAMES

Reinforced extruded aluminium bottom rail section

Heavy duty extruded aluminium guide rails anchored direct to the structure



## SUBSTRATES

Certified installation onto:

Blockwork

Concrete

Structural Steelwork

Timber

Sub assembly steel framework

## CONTROLS

Range of compatible controls including rotary switch, key switch, remote (control) and emergency manual crank

Integration with 3rd Party access control system

Safety supplied as design risk assessment directs