

# 700 SERIES DATA SHEET



## BOLT ON SECURITY SHUTTERS



### FEATURES

- Compact roll zones
- High strength and low weight
- Twin skin extruded aluminium lath
- Polyester powder coated to any standard RAL /BS colour

### OPTIONS

- Range of switches and access control
- Can be partially or fully perforated and punched

### ALL-ALUMINIUM CONSTRUCTION

- Twin part roll formed aluminium casing
- Slimline extruded aluminium guides
- Smooth and quiet operation with roller guide entry

### TYPICAL APPLICATIONS

Suitable new build applications include:

- Medium risk commercial buildings
- Public facilities - schools, universities, community centers, pavilions
- Retail outlets - point of sale gantries
- Cultural Buildings
- Residential

# 700 SERIES DATA SHEET



## BOLT ON SECURITY SHUTTERS

### PRODUCT REFERENCE

Xonar 700 Security Shutter

### APPROVED DIMENSIONS

Maximum width: 3.2m

Maximum height: 4.0m

Minimum width: 1.0m

Minimum height: 1.0m

### SHUTTER CURTAIN

40mm twin wall.

Extruded aluminium profiles.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

Option to fully or partially perforate or punched.

### OPERATION

Motorised to allow controlled ascent and descent.

Tube Motor - Low duty cycle, or where limited to single phase supply.

External Drive Motor - High duty cycle or for larger apertures.

### FRAMES/GUIDES

Slimline extruded aluminium guides mounted directly to structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.



### SUBSTRATE

Installation onto:

Brickwork

Blockwork

Steelwork

Timber

### BOTTOM RAIL

Extruded aluminium section with rubber sealing gasket.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

### CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms.

Safety on close as assessment directs.

Battery backup options.

Distributor

