

710 SERIES DATA SHEET



BOLT ON SECURITY SHUTTERS WITH SELF-LOCKING TECHNOLOGY



FEATURES

- Compact roll zones
- Twin skin extruded aluminium lath
- Self locking technology
- Polyester powder coated to any standard RAL /BS colour



OPTIONS

- Range of switches and access control
- Can be partially or fully perforated



ALL-ALUMINIUM CONSTRUCTION

- Twin part roll formed aluminium casing
- Slimline extruded aluminium guides
- Smooth and quiet operation with roller guide entry



TYPICAL APPLICATIONS

Suitable new build applications include:

- Medium to high risk commercial buildings
- Public facilities - schools, universities, community centers, pavilions
- Retail outlets - point of sale gantries
- Cultural Buildings
- Residential



710 SERIES DATA SHEET



BOLT ON SECURITY SHUTTERS WITH SELF-LOCKING TECHNOLOGY

PRODUCT REFERENCE

Xonar 710 Security Shutter

APPROVED DIMENSIONS

Maximum width: 3.2m

Maximum height: 4.0m

Minimum width: 1.0m

Minimum height: 1.0m

SHUTTER CURTAIN

40mm twin wall self locking lath.

Extruded aluminium profiles.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

Option to fully or partially perforate.

OPERATION

Motorised to allow controlled ascent and descent.

Tube Motor - Low duty cycle, or where limited to single phase supply.

External Drive Motor - High duty cycle or for larger apertures.

FRAMES/GUIDES

Slimline extruded aluminium guides mounted directly to structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.



SUBSTRATE

Installation onto:

Brickwork

Blockwork

Steelwork

Timber

BOTTOM RAIL

Extruded aluminium section with rubber sealing gasket.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms.

Safety on close as assessment directs.

Battery backup options.

Distributor

