



8 x grid adaptors



**DM298GRID**  
LED mains grid dimmer




Product code	DM298GRID
Construction material	Plastic
Dimmer type	Push on / off, rotary dial dim
Grid plate adaptors	White adaptors for Hamilton, MK, BG, Crabtree, Schneider, DETA, Hager & Wandsworth grid ranges
Mains supply voltage	240V AC
Mains supply voltage range	230V AC - 240V AC
Mains supply frequency	50Hz
Load type	LED dimmable driver only
Minimum load capacity	5W
Maximum load capacity	100W / 10 LED units max.
Phase firing	Trailing edge dimming
Connection terminals	3mm <sup>2</sup> max.
Back box depth	35mm min.
Guarantee	1-year

**USE IN CONJUNCTION WITH**

H2 Lite	65
H2 Lite 500	66
H2 Lite 500 CSW	67
H2 Lite 500 CSP	68
H2 Pro 550 (T)	69
H2 Pro 550 SPS	70
H2 Pro 550 CS	71
H2 Pro 700	72
H2 Pro Dusk	73
H2 Pro Elect	74
H2 Pro Elect Trimless	75
H4 Pro 550	77
H4 Pro 550 SPS	78
H4 Pro 700	79
H4 Pro Elect	80
H5 Trimless	82
H5 500 Symmetric	83
H5 500 Asymmetric	84
H5 1000 Symmetric	85
H5 1000 Asymmetric	86
H6 Lite	87
DL201	94
DL120 / DL130	97
FIBRE LED LIGHT	98
RL111	100
DM02	102

- > Compatible with the downlight range
- > Minimum brightness can be adjusted
- > Minimum depth of pattress box: 35mm
- > Complete with ring nut and white plastic dimmer knob
- > Complete with white plastic grid plates
- > BS EN 60669-2-1
- > 10 LED units max.



**DM298FP**  
Faceplate dimmer



Product Code	DM298FP
Construction material	Plastic
Dimmer type	Push on / off, rotary dial dim
Grid plate adaptors	-
Mains supply voltage	240V AC
Mains supply voltage range	230V AC - 240V AC
Mains supply frequency	50Hz
Load type	LED dimmable driver only
Minimum load capacity	5W
Maximum load capacity	100W / 10 LED units max.
Phase firing	Trailing edge dimming
Connection terminals	3mm <sup>2</sup> max.
Back box depth	35mm min.
Guarantee	1-year

**USE IN CONJUNCTION WITH**

H2 Lite	65
H2 Lite 500	66
H2 Lite 500 CSW	67
H2 Lite 500 CSP	68
H2 Pro 550 (T)	69
H2 Pro 550 SPS	70
H2 Pro 550 CS	71
H2 Pro 700	72
H2 Pro Dusk	73
H2 Pro Elect	74
H2 Pro Elect Trimless	75
H4 Pro 550	77
H4 Pro 550 SPS	78
H4 Pro 700	79
H4 Pro Elect	80
H5 Trimless	82
H5 500 Symmetric	83
H5 500 Asymmetric	84
H5 1000 Symmetric	85
H5 1000 Asymmetric	86
H6 Lite	87
DL201	94
DL120 / DL130	97
FIBRE LED LIGHT	98
RL111	100
DM02	102

- > Compatible with the downlight range
- > Minimum brightness can be adjusted
- > Minimum depth of pattress box: 35mm
- > Complete with ring nut, white plastic dimmer knob and faceplate
- > BS EN 60669-2-1
- > 10 LED units max.

