



FEATURES & BENEFITS

- Provides minimum of 3 hours of emergency lighting
- Green light indicates charging of batteries
- Pre-wired service offers peace of mind and reduces installation time

LEDEP06 folded



LEDEP06 unfolded



LEDEP06

LED emergency pack for maintained lighting assembly - 3hr minimum emergency lighting



Suitable for use indoors



3-year guarantee on LED driver
1-year guarantee on battery



ELECTRICAL CHARACTERISTICS

Product code	W	Input (mA)	Input (V)	Output (mA)	Output (V)
LEDEP06	3	40 maximum	220V-240V 50-60Hz	4 - 470	6 - 55

GENERAL

Double insulation	Yes
Case temperature (tc = °C)	70
Inrush current	20A 0.012ms

WIRING

Connection output	Terminals
Input cable required	0.2 - 1.5mm ²

EMERGENCY PACK SERVICE OPTION

Approx. 25% light output compared to normal running

For full product codes of pre-wired emergency pack service option see relevant specification sheet

Product	Description
H2 Pro 550 SPS	Single point source, dimmable, fire-rated LED downlight
H2 Pro 550 CS*	Colour switchable, dimmable, fire-rated LED downlight
H2 Pro 700	Dimmable, fire-rated LED downlight
H2 Pro Dusk	Dim to warm, fire-rated LED downlight
H2 Pro Elect	Low glare, dimmable, fire-rated LED downlight
H2 Pro Elect Trimless	Low glare, plaster-in, trimless, dimmable, fire-rated LED downlight
H4 Pro 550 SPS	Adjustable, single point source, dimmable, fire-rated LED downlight
H4 Pro 700	Adjustable, dimmable fire-rated LED downlight
H4 Pro Elect	Adjustable, low glare, dimmable, fire-rated LED downlight
H5 500 Symmetric	Low glare, fire-rated LED downlight
H5 500 Asymmetric	Low glare, fire-rated LED downlight

*3000K when operating in emergency mode

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

LED

874/2012