



FEATURES & BENEFITS

- › Provides minimum of 3 hours of emergency lighting
- › Green light indicates charging of batteries
- › Pre-wired service offers peace of mind and reduces installation time

LEDEP07

LED emergency pack for maintained lighting assembly - 3hr minimum emergency lighting

IP20

Suitable for use indoors

3yr 1yr

3-year guarantee on LED driver
1-year guarantee on battery

±55°C

420g

ELECTRICAL CHARACTERISTICS

Product code	W	Input (mA)	Input (V)	Output (mA)	Output (V)
LEDEP07*	3	40 maximum	220V-240V 50-60Hz	8 - 60	50 - 200

* Must be purchased as part of Collingwood's pre-assembled emergency pack service, see relevant product page

GENERAL

Double insulation	Yes
Case temperature (tc = °C)	70
Inrush current	20A 0.012ms

WIRING

Connection output	Terminals
Flying leads	300mm 2-core 0.75mm ²

EMERGENCY PACK SERVICE

Approx. 25% light output compared to normal running

For full product codes of pre-wired emergency pack service see relevant specification sheet

Product	Description
H2 Pro 550	Dimmable, fire-rated LED downlight
H4 Pro 550	Adjustable, dimmable fire-rated LED downlight

LEDEP07 folded



LEDEP07 unfolded

