




COLLINGWOOD
LIGHTING




FEATURES & BENEFITS

- › Complete with wall fixings
- › Robust cable for use outdoors
- › Tilt & rotate for adjusting light



4000K 26°
Additional diagrams available at collingwoodlighting.com



UL010

Universal LED light



Submersible to 9m



7-year extended warranty available



Also available in RGBW See page 271



Patent information: collingwoodlighting.com/patent

ZONE L70, B10

35DCM

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
4000K	26°	UL010 NW	>80Ra	140	70	393
3000K	26°	UL010 WW	>80Ra	135	68	379
2700K	26°	UL010 27*	>80Ra	120	60	337
Blue	26°	UL010 BL	-	-	-	-

*Available on request, please call our team for lead times and MOQ on 01604 495 151

GENERAL

Construction material: Stainless steel (316)

WIRING

Cable / flying lead: 3 (H05RN-F) rubberised cable (outside diameter: 6mm)

Type of wiring required: Series

LED DRIVERS

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	700	Yes	No	1	3	9
PL/IP/700 1-3	700	Yes	No	0	1	3
PLD UNI-DRIVE 700MA	700	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

Product code	Description
JB2 / JB4	Waterproof junction box / Gel filled waterproof connector
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
WCR 275 BLACK	2-core rubber cable

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

LED

A++ A+ A C D E

874/2012

