



FEATURES & BENEFITS

- › Surface mount in multiple applications
- › Full RGB colour range
- › Compatible with a large range of controllers
- › Anodised aluminium for use in outdoor and indoor environments
- › Removable feet can be used anywhere along the base or sides. Allen key included

UL345CARGB

110° colour change LED wall washing light bar (12W max.)



Ideal for use outdoors



5-year extended warranty available



ZONE



L50, B50

PHOTOMETRICS @ 25°C

LED RGB units are designed for colour change. They are not suitable for running on permanent white for long periods of time

Colour	Beam angle	Product code	W	CRI	lm	lm/W	lx at 1m
Red	110°	UL345CARGB	4	-	96	24	20
Green	110°		4.1	-	161	39	58
Blue	110°		4.3	-	51	12	0

GENERAL

Construction material Anodised aluminium

WIRING

Cable / flying lead 1x 3m LED RGB 0.75mm² cable (outside diameter: 6mm)

Type of wiring required N/A (1 per power repeater)

LED DRIVERS (power repeaters)


Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PR3011	350	-	Yes	1	1	1

ACCESSORIES

For complete range of colour change controllers see page 254-257

Product code	Description
JB3	Colour change extension lead for RGB products
LED RGB 0.75 CABLE	4-core PVC cable
ULBRACKET	2 piece black anodised aluminium bracket



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

A++ A+ A C D E

LED

874/2012