



SOVEREIGN SOLOFLOOD PROJECTOR S18394

PRODUCT DETAILS

RANGE NAME	SOVEREIGN SOLOFLOOD PROJECTOR
CATALOGUE NUMBER	S18394
APPLICATION	INTERIOR SURFACE
LIGHT SOURCE	TRIDONIC LLE LED
LAMP LIFE	50,000 HOURS
COLOUR RENDERING (RA)	>80
VOLTAGE	240V
PROTECTION RATING	CLASS 1
DRIVER	INTEGRATED HIGH EFFICIENCY
IP RATING	IP20
HOUSING MATERIAL	ALUMINIUM
MATERIAL FINISH	POWDER COATED
WEIGHT	2.8KG
LED WARRANTY	5 YEARS
ADDITIONAL	ACCESSORIES

CUSTOMISATION OPTIONS

MOUNTING	TRACK ADAPTER / CEILING PLATE
HOSUING COLOUR	WHITE / OTHER BS/RAL COLOUR
COL. TEMP	3000K / 4000K
OUTPUT	VARIOUS
DIMMABILITY	DIMMABLE OPTIONS AVAILABLE
ADDITIONAL	BARN DOORS / LOUVRE

LIGHT OUTPUT DETAILS

Col. Temp	Wattage	Lumen Output	LED Efficacy
3000K	25.5W	4060lm	159lm/W
4000K	25.41W	4240lm	167lm/W

ORDER CODE

STYLE	MOUNTING	HOUSING COLOUR	COL TEMP	DIMMABILITY
S18394 SOLOFLOOD	[BLANK] STIRRUP ONLY	.05 WHITE	00 3000K	[BLANK] NON DIMMING
	TR TRACK ADAPTER	.04 BLACK	01 4000K	/101 1-10V DIMMING
	CP CEILING PLATE	.21 SILVER		/102 DALI DIMMING
				/103 MAINS DIMMING
				/104 DSI DIMMING
				/105 SWITCH DIM
				/106 DMX

Disclaimer text:
Commercial Lighting Systems Ltd uses quality components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Commercial Lighting is continually developing and improving its products and reserves the right to change technical specifications without prior notice.