



Line Paint

High Visibility Epoxy Line Marking

USES

Line Paint provides durable, hardwearing, easily cleaned, dustfree and attractive demarcation lines in areas where an abrasion and chemical resistant line is required. Line paint is suitable for use as a line marking in a wide range of industrial environments including chemical process areas, food and beverage processing plants, dairies, pharmaceutical plants, production workshops and warehousing areas.

DESCRIPTION

Line Paint is a two-pack high build epoxy coating formulated to provide excellent finish and application properties which cure to form a tough easily cleaned gloss finish. A light reflective grade is also available.

ADVANTAGES

High visibility	brightly coloured
Chemically resistant	excellent resistance to a wide range of industrial Chemical
Hygienic	impervious, dustfree, easily cleaned surface
Durable	good abrasion resistance
Low odour	low odour formulation
Proven performance	long standing job references
Ease of application	trained staff can achieve excellent application rates

PHYSICAL PROPERTIES

Specific Gravity	1.5
Pot Life	30-40 mins
Cure Time	8-16 hours
Time Between Coats	12 hours
Initial Hardness	12 hours
Open to Light Traffic	24 hours
Full Cure	7 days
(Below 20° C these times will be increased)	

CHEMICAL RESISTANCE

Line Paint is resistant to a wide range of chemicals. Specific data is available on request.



COLOURS

Line Paint is available in a range of four colours, White, Gold, Black and Poppy Red.

TEMPERATURE

Line Paint should not be applied at temperatures below 10° C and above 40° C

INSTRUCTIONS FOR USE

Painted surfaces should be clean, dry and any loose or flaking material removed and sanded down to a sound base

MIXING AND APPLICATION

Line Paint is a two pack system supplied in pre-weighed units ready to mix. Line Paint is applied by brush or roller, after areas to be lined have been marked out using masking tape.

COVERAGE AND PACK SIZES

Pack Size kg	Pack Size ltr	Approx. Coverage Per Coat
1kg	0.75 ltr	60 lin. m per 1kg @75mm wide
2kg	1.45 ltr	120 lin. m per 2kg @75mm wide

PRECAUTIONS

Line Paint is a non-flammable product. Line Paint should not be allowed to come into contact with skin and eyes or be swallowed. Epoxy resins and hardeners may act as skin sensitizers to some people. Gloves, goggles and a suitable barrier cream should therefore be used. Ensure adequate ventilation if working in enclosed areas. Skin contamination with any of the products should be removed immediately with soap and water. In the event that mixed Line Paint comes into contact with the skin, it must be removed before it hardens with a good quality resin removing cream, followed by washing with soap and water. Do not use solvent. If accidental eye contamination occurs irrigate with copious quantities of clean water and seek medical advice. If ingestion of any of the materials takes place, seek medical attention immediately. Do not induce vomiting.

DISPOSAL

All tools and equipment should be cleaned with water immediately after use. Spillage should be absorbed with sand or sawdust and disposed of in accordance with statutory regulations.

STORAGE

Shelf life at least 12 months if stored in original containers between 10° C and 25° C.

CONTRACTING SERVICE

Conren Limited offer a contracting service for the application of all Conren products. This facility is backed by a comprehensive technical and after sales service. We are able to contend with most problems in the field.

TECHNICAL SERVICE & QUALITY ASSURANCE

All information provided in this leaflet is based on results obtained from our own experience and test and is given in good faith. The user will be deemed to have satisfied himself independently of the suitability of Conren's products for his own particular purpose. We guarantee to replace, free of charge, any goods supplied by us which are proved to our satisfaction defective, but, as the application of these materials is necessarily beyond our control, we will not accept responsibility for any damage or loss arising wholly or in part from these materials. Except as herein provided, any express or implied condition, warranty, statement or representation, statutory or otherwise as to the quality of the goods is expressly excluded.

SPECIFICATION

Demarcation to floors shall be Conren Line Paint.

All products to be applied in accordance with Conren's written instructions.

Conren Limited
Unit 1
The Bridge Business Centre
Ash Road South
Wrexham Industrial Estate
Wrexham
LL13 9UG
Tel: +44 (0) 1978 661 991
Fax: + 44 (0) 1978 664 664
e-mail: info@conren.com
web: www.conren.com